ACDelco | 2019 FLUIDS AND CHEMICALS CATALOG

KEEPING AMERICA MOVING WITH QUALITY, VALUE AND CONFIDENCE



| The ACDelco Fluids and Chemicals Catalog—your source for the automotive chemicals your team needs to help keep your customers' vehicles running For more than 100 years, ACDelco has been supplying the right combination products designed to maintain vehicle life. | smoothly. |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|
| | |
| | |



FLUIDS & CHEMICALS CATALOG TABLE OF CONTENTS

| PR | n | n | Ш | דח | C |
|----|---|---|---|----|---|
| ΓN | U | υ | U | וט | J |

| Adhesives | 7 |
|------------------------------|----|
| Air Conditioning | 10 |
| Antifreeze/Coolants | 13 |
| Appearance | 16 |
| Axle Lubes/Fluids | 24 |
| Body Shop | 27 |
| Brake Fluids and Cleaners | 28 |
| Carb/Choke Cleaner | 30 |
| Diesel Exhaust Fluid | 31 |
| Fuel System | 33 |
| Leak Detect | 35 |
| Lubricants/Greases | 36 |
| Motor Oils (Plus Supplement) | 43 |
| Paints | 44 |
| Power Steering Fluids | 45 |
| Sealants | 46 |
| Transmission Fluids | 50 |
| Safety Data Sheets | 57 |

Product specifications and descriptions were correct at the time this catalog was printed. ACDelco reserves the right to improve, discontinue, or change any part of the copy, photography, and parts without notice.

ALPHABETIC INDEX

| Item | Page | Item | Page |
|------------------------------------------------------------|------|-----------------------------------------------------|------|
| Adhesion Promoter | 7 | Leather and Vinyl Conditioner | 19 |
| Glass Adhesion Promoter - Aerosol | 7 | Leather and Vinyl Conditioner | 19 |
| High-Strength-Slip Fit Retaining Compound | 7 | Leather, Vinyl and Plastic Cleaner | 19 |
| Hot Melt Adhesive Sticks | 7 | Leather, Vinyl and Plastic Cleaner | 19 |
| Instant Gel Adhesive | 8 | Microfiber Towel (Ultra Fine) | 20 |
| Metal Patch Panel Adhesive | 8 | Odor Eliminator | 20 |
| Plastic Installation Adhesive | 8 | Odor Eliminator | 20 |
| Plastic Repair Adhesive (High-Strength) | 8 | Optikleen® (Windshield Washer Solvent) | 20 |
| Rearview Mirror Adhesive | 8 | Optikleen® (Windshield Washer Solvent) | 20 |
| Structural Bonding Expoy - Cartridge | 9 | Optikleen® (Windshield Washer Solvent) | 21 |
| Structural Metal Bonding Adhesive | 9 | Quick Detailer | 21 |
| Structural Urethane Installation Adhesive | 9 | Rain Repellent Treatment | 21 |
| Tape | 9 | Stainless Steel and Chrome Cleaner and Polish | 21 |
| Weather Strip Adhesive Gel - Black | 9 | Touch Screen Cleaner | 21 |
| Air Conditioner Compressor Oil PAG-SPA2 (R-1234yf) | 10 | Three Piece Vehicle Cleaning Kit | 22 |
| Air Conditioner Compressor Oil | 10 | Upholstery/Carpet Stain Remover - Gold Formula | 22 |
| Air Conditioning Compressor Oil (46 Viscosity) - Cartridge | 10 | Upholstery/Carpet Stain Remover - Gold Formula | 22 |
| Air Conditioning Compressor Oil (525 Viscosity) | 10 | Upholstery/Carpet Stain Remover - Red Formula | 22 |
| Air Conditioning Oil POE | 10 | Upholstery/Carpet Stain Remover - Red Formula | 22 |
| Air Conditioning (A/C) System Dye | 11 | Vinyl, Rubber and Tire Dressing | 23 |
| Cooling Coil Coating - Refill for Applicator Kit | 11 | Vinyl, Rubber and Tire Dressing | 23 |
| Cooling Coil Coating Applicator Kit | 11 | Wheel and Rim Cleaner | 23 |
| R-1234yf Refrigerant | 11 | White Sidewall Cleaner | 23 |
| R-134a Refrigerant | 11 | Auto Trak II Transfer Case Fluid | 24 |
| R-134a Refrigerant | 12 | Axle Lubricant GL-5 (80W-90) | 24 |
| R-134a Refrigerant | 12 | DEXRON® Gear Fluid (75W-90) | 24 |
| Refrigerant Oil (150 Viscosity) | 12 | DEXRON® LS Gear Oil (75W-90) | 24 |
| CE Extended Life (Blue) Prediluted Antifreeze/Coolant | 13 | Limited Slip Axle Lubricant Additive | 24 |
| Cooling System Seal Tabs | 13 | Limited Slip Axle Lubricant Additive | 25 |
| DEX-COOL® 50/50 Premix | 13 | Rear Axle Lubricant - High Efficiency GL-5 (75W-85) | |
| DEX-COOL® 50/50 Premix | 13 | Rear Axle Lubricant - High Efficiency GL-5 (75W-85) | 25 |
| DEX-COOL® 50/50 Premix | 14 | Synthetic Axle Lubricant GL-5 (75W-90) | 25 |
| DEX-COOL® Concentrate | 14 | Synthetic Axle Lubricant GL-5 (75W-90) | 25 |
| DEX-COOL® Concentrate | 14 | Snythetic Transfer Case Fluid | 26 |
| DEX-COOL® Concentrate | | Synthetic Axle Gear Lubricant GL-5 (75W-140) | 26 |
| Radiator Fast Flush + Cleaner | 15 | Synthetic Gear Oil GL-5 (75W-140) | 26 |
| Traditional Coolant Concentrate | 15 | Transfer Case Fluid | 26 |
| Traditional Coolant Concentrate | 15 | VERSATRAK® Fluid GL-5 (75W-85) | |
| Traditional Coolant Concentrate | 15 | Anti-Corrosion Compound (Wax-Based) - Aerosol | 27 |
| Car Wash Shampoo | 16 | Rubberized Undercoating - Aerosol | |
| Car Wash Shampoo | 16 | Rust and Corrosion Inhibitor - Aerosol | |
| Car Wash Shampoo | | Rust Penetrant and Inhibitor - Aerosol | |
| Chevrolet Vehicle Care Kit | | Sound Deadening Pad Package | |
| Corvette Vehicle Care Kit | | Brake and Clutch Fluid, DOT 3 GMW | |
| GM Vehicle Care Kit - Large | | Brake and Clutch Fluid, DOT 4 GMW | |
| GM Vehicle Care Kit - Small | | Brake Parts Cleaner (10% VOC) - Aerosol | |
| GMC Vehicle Care Kit - Large | | Brake Parts Cleaner (10% VOC) | |
| Cleaner Wax | | Brake Parts Cleaner (45% VOC) - Aerosol | |
| Cleaner Wax | | Brake Parts Cleaner (45% VOC) | |
| Cloth/Carpet Cleaner Concentrate | | Carburetor and Choke Cleaner (10% VOC) - Aerosol | |
| Glass Cleaner - Aerosol | | Carburetor Tune-Up Conditioner - Aerosol | |
| Glass Cleaner - Aerosol | | Diesel Exhaust Fluid | |
| Interior Cleaner Brush | 19 | Diesel Exhaust Fluid | 31 |

ALPHABETIC INDEX

| Item | Page | ltem I | Page |
|---------------------------------------------------|------|-------------------------------------------------------------|------|
| Diesel Exhaust Fluid | 31 | Four-in-One Assortment Kit | 42 |
| Diesel Exhaust Fluid | | Four-in-One Paint Rack | |
| Diesel Exhaust Fluid - Nozzle | | High Gloss Black Engine Enamel Paint - Aerosol | |
| Diesel Exhaust Fluid - Nozzle | | Low Gloss Black Engine Enamel Paint - Aerosol | |
| Disel Fuel Conditioner | | Reconditioning Paint (Black/Aqua) - Aerosol | |
| Fuel System Treatment Plus - Disel | | Reconditioning Paint (Gray/White) - Aerosol | |
| Fuel System Treatment Plus - Flex Fuel | | Cold Climate Power Steering Fluid | |
| Fuel System Treatment Plus - Gasoline | | Cold Climate Power Steering Fluid | |
| Top Engine Cleaner - Aerosol | | Electro-Hydraulic Power Steering Fluid | |
| Top Engine Cleaner - Aerosol | | Power Steering Fluid | |
| Coolant System Fluorescent Tracer Dye | | Power Steering Fluid | |
| Coolant System Tracer Dye | | Anti-Corrosion Wax Sealant | |
| Fluorescent Dye, 4-in-1 | | Flange Sealant | |
| Fluorescent Tracer Dye Injector Package (Tool) | | Gasket Maker Sealant | |
| Ultra Violet (UV) Lamp Bulb - 12 Volt DC | | Gasket Sealing Compound | |
| Ultra Violet (UV) Leak Detector Lamp Kit | | High-Strength, High-Temperature Threadlocker - Red | |
| | | | |
| Anti-Seize Lubricant | | Medium Body Seam Sealing Compound | |
| ATE Plastilube Grease | | Medium-Strength Threadlocker - Blue | |
| Brake Caliper Lubricant - Cartridge | | RTV Flange Sealant 5970 | |
| Chassis Grease - Cartridge | | RTV Pink Flange Sealant | |
| Dielectric Lubricant | | RTV Slicone Sealant - Cartridge | |
| Dielectric Silicone Grease | | RRV Silcone Sealant - Tube | |
| E.O.S. Assembly Lubricant | | RTV Heavy Body Silicone Sealant - Cartridge | |
| Gear Marking Compound | | RTV Sealant | |
| High Temperature Grease | | RTV Silicone Sealant - Red - Tube | |
| Hydraulic Fluid (Aeroshell 41) | | RTV Silicone Sealant - RTV 5900 - Power Can | |
| Multi-Purpose Lubricant - Aeroso | | RTV Sliclone Sealant | |
| Hydraulic Pump Fluid | | Sealant | |
| Hydraulic Pump Fluid | | Thread Sealant - Tube | |
| Low Temperature Synthetic Dampening Grease | 38 | Automatic Transmission Fluid | |
| M-77 Paste | | Automatic Transmission Seal Conditioner | |
| Moisture Displacing Lubricant - Aerosol | 38 | AW-1 Automatic Transmission Fluid | |
| Molykote CU-7439 | | BOT 303 Modified Manual Transmission Fluid GL-4 (SAE 70W) . | 50 |
| Multi-Purpose Grease (Aerosol) | | CVT Fluid | |
| Multi-Purpose Lubricant with PTFE - Cartridge | 39 | CVT Fluid | 51 |
| Nickel Anti-Seize Lubricant | 39 | DEXRON® ULV Automatic Transmission Fluid | 51 |
| P-80 Emulsion Temporary Rubber Assembly Lubricant | 39 | DEXRON®-VI Automatic Transmission Fluid | 51 |
| PTFE Grease-High Viscosity | 40 | DEXRON®-VI Automatic Transmission Fluid | 51 |
| PTU Synthetic Lubricant (75W-90) | 40 | DEXRON®-VI Automatic Transmission Fluid | 51 |
| Rear Differential Clutch Fluid GL-4 (75W-90) | 40 | Manual Transmisison and Transfer Case Fluid | 52 |
| Rubber Lubricant | 40 | Manual Transmission Fluid GL-3 (75W-90) | 52 |
| Rubber Lubricant | 40 | Manual Transmission Fluid GL-4 (SAE 75W-85) | 52 |
| Silicone Brake Lubricant | 41 | Manual Transmission Fluid GL-4 (SAE 75W-85) | 52 |
| Silicone Dielectric Grease | 41 | Synchromesh Transmission Fluid | 52 |
| Super Lube® with PTFE - Aerosol | 41 | Synchromesh Transmission Fluid-Friction Modified | 53 |
| Super Lube® with PTFE | 41 | Synthetic Manual Transmission Fluid GL-4 (75W-90) | |
| Supercharger Oil | | Synthetic Transmission Fluid | |
| Synthetic Grease | | WS-ATF Automotive Transmission Fluid | |
| Synthetic Multi-Purpose Lubricant | | | |
| Weatherstrip Lubricant | | | |
| Wheel Bearing and Chassis Lubricant | | | |
| Wheel Speed Sensor Anti Corrosion Grease | | | |

dexos2 TM 5W-30......43

ACDELCO NUMERICAL INDEX

| Item | Page | Item | Page | Item | Page | Item | Page |
|--------------------|------|--------------------|------|--------------------|------|----------------------|------|
| 10-101 | 14 | 10-4026 | 31 | 10-4111 | 40 | 10-8034 | 23 |
| 10-105 | 35 | 10-4027 | 31 | 10-4112 | 10 | 10-8035 | 19 |
| | 13 | 10-4029 | 53 | 10-4113 | 52 | 10-8042 | 16 |
| 10-125 | 14 | 10-4032 | 25 | 10-4114 | 38 | 10-8043 | 16 |
| 10-1007 | 9 | 10-4033 | 52 | 10-4116 | 42 | 10-8044 | 16 |
| 10-1010 | 8 | 10-4034 | 24 | 10-4119 | 53 | 10-8045 | 18 |
| 10-1011 | 7 | 10-4037 | 50 | 10-4642 | 42 | 10-8046 | 18 |
| 10-1012 | 9 | 10-4038 | 39 | 10-5026 | 10 | 10-8047 | 21 |
| 10-1013 | 8 | 10-4039 | 39 | 10-5027 | 13 | 10-8048 | 23 |
| 10-1014 | 8 | 10-4040 | 37 | 10-5032 | 15 | 10-8050 | 23 |
| 10-1015 | 8 | 10-4041 | 41 | 10-5034 | 15 | 10-8051 | 23 |
| 10-1016 | 9 | 10-4044 | 26 | 10-5038 | 14 | 10-8063 | 20 |
| 10-1017 | 27 | 10-4045 | 38 | 10-5041 | 37 | 10-8070 | 21 |
| 10-1019 | 7 | 10-4048 | 37 | 10-5043 | 45 | 10-8073 | 21 |
| 10-1020 | 8 | 10-4049 | 53 | 10-5044 | 45 | 10-8074 | 22 |
| 10-1021 | 46 | 10-4051 | 24 | 10-5045 | 35 | 10-8076 | |
| 10-1022 | 7 | 10-4053 | 26 | 10-5046 | | 10-9129 | 43 |
| 10-1023 | 7 | 10-4054 | | 10-5050 | 45 | 10-9255 | 11 |
| 10-2006 | | 10-4055 | | 10-5051 | | 10-9394 | |
| 10-2010 | 47 | 10-4056 | | 10-5052 | | 10-9395 | |
| 10-2011 | | 10-4057 | | 10-5055 | | 10-9396 | 51 |
| 10-2012 | | 10-4058 | | 10-5056 | | | 10 |
| 10-2013 | | 10-4060 | | 10-5057 | | | 12 |
| 10-2017 | | 10-4062 | | 10-5057 | | | 12 |
| 10-2018 | | 10-4063 | | 10-5070 | | 15-119A | |
| 10-2019 | | 10-4064 | | 10-5071 | | 15-91244 | |
| 10-2020 | | 10-4066 | | 10-5072 | | 1 7 7 | 30 |
| 10-2022 | | 10-4067 | | 10-5073 | | 01051515 | |
| 10-2023 | | 10-4070 | | 10-5074 | | 12346241 | |
| 10-2024 | | 10-4071 | | 10-6005 | | 12346668 | |
| 10-2024 | | 10-4072 | | 10-6006 | | 12377979 | |
| 10-2025 | | 10-4074 | | 10-6013 | | 12378112 | |
| 10-2026 10-2027 | | 10-4075 10-4077 | | 10-6014 10-6016 | | 12378134 12378136 | |
| 10-2027 | | 10-4077 | | 10-6026 | | 12378454 | |
| 10-2028 | | 10-4078 | | 10-6027 | | 19260234 | |
| 10-3011 | | 10-4086 | | 10-7011 | | 19368258 | |
| 10-3012 | | 10-4091 | | 10-7012 | | 88863899 | |
| 10-3013 | | 10-4092 | | 10-7013 | | 89021958 | |
| 10-3014 | | 10-4094 | | 10-7015 | | 03021300 | ∠⊣ |
| 10-3015 | | 10-4095 | | 10-8016 | | | |
| 10-4003 | | 10-4096 | | 10-8017 | | | |
| 10-4006 | | 10-4097 | | 10-8018 | | | |
| 10-4014 | | 10-4098 | | 10-8020 | | | |
| 10-4016 | | 10-4099 | | 10-8025 | | | |
| 10-4017 | 24 | 10-4100 | | 10-8026 | | | |
| 10-4019 | | 10-4103 | | 10-8027 | | | |
| 10-4020 | | 10-4104 | | 10-8028 | | | |
| 10-4021 | | 10-4105 | | 10-8029 | | | |
| 10-4022 | 31 | 10-4106 | | 10-8030 | | | |
| 10-4023 | 31 | 10-4107 | 51 | 10-8031 | 22 | | |
| 10-4024 | 32 | 10-4108 | 24 | 10-8032 | 22 | | |
| 10-4025 | 32 | 10-4110 | 28 | 10-8033 | 22 | | |
| | | 1 | | 1 | | • | |

GM NUMERICAL INDEX

| 01050026 46 12378567 9 19368179 7 88865597 01050175 23 12378568 9 19368258 44 88865601 01051344 42 19245469 48 19369226 53 88865602 01051498 44 19256039 50 22717466 50 88865603 01051499 44 19257121 42 88844067 21 88865785 01051515 20 19257664 27 88861039 8 88865945 01052351 37 19259104 50 88861206 35 8886142 01052626 34 19370291 18 88861314 50 88900330 01052948 37 19260234 11 88861401 19 88900333 03634770 42 19260800 50 88861402 19 88900399 12302498 30 19286291 31 88861403 22 88900402 12345507 | 515151212119525253254949 |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------|
| 01050175 23 12378568 9 19368258 44 88865601 01051344 42 19245469 48 19369226 53 88865602 01051498 44 19256039 50 22717466 50 88865603 01051499 44 19257121 42 88844067 21 88865785 01051515 20 19257664 27 88861039 8 88865945 01052351 37 19259104 50 88861206 35 88886142 01052626 34 19370291 18 88861314 50 88900330 01052948 37 19260234 11 88861401 19 88900333 03634770 42 19260800 50 88861402 19 88900399 12301108 10 1926091 41 88861403 22 88900401 12344968 35 19286292 31 88861404 22 88900402 12345579 36 19286318 32 88861406 19 88901975 | 51512119525253252524104549 |
| 01051344 42 19245469 48 19369226 53 88865602 01051498 44 19256039 50 22717466 50 88865603 01051499 44 19257121 42 88844067 21 88865785 01051515 20 19257664 27 88861039 8 88865945 01052351 37 19259104 50 88861206 35 88886142 01052626 34 19370291 18 88861314 50 88900330 01052948 37 19260234 11 88861401 19 88900333 03634770 42 19260800 50 88861402 19 88900399 12301108 10 19260901 41 88861403 22 88900401 12344968 35 19286291 31 88861405 19 88901445 12345097 9 19286318 32 88861406 19 88901975 12345726 9 19287400 29 88861408 22 89020330 | 51512119525253252524104549 |
| 01051499 44 19257121 42 88844067 21 88865785 01051515 20 19257664 27 88861039 8 88865945 01052351 37 19259104 50 88861206 35 88886142 01052626 34 19370291 18 88861314 50 88900330 01052948 37 19260234 11 88861401 19 88900333 03634770 42 19260800 50 88861402 19 88900399 12301108 10 19260901 41 88861403 22 88900401 12302498 30 19286291 31 88861404 22 88900402 12345097 9 19286318 32 88861406 19 88901975 12345579 36 19286319 32 88861406 19 89020326 12345726 9 19287400 29 88861408 22 89020330 12345866 45 19287401 28 88861420 18 89021329 <td>21212552532524104549</td> | 21212552532524104549 |
| 01051515 20 19257664 27 88861039 8 88865945 01052351 37 19259104 50 88861206 35 88886142 01052626 34 19370291 18 88861314 50 88900330 01052948 37 19260234 11 88861401 19 88900333 03634770 42 19260800 50 88861402 19 88900399 12301108 10 19260901 41 88861403 22 88900401 12302498 30 19286291 31 88861404 22 88900402 12344968 35 19286292 31 88861405 19 88901445 12345097 9 19286318 32 88861406 19 88901975 12345579 36 19286319 32 88861407 22 89020326 12345726 9 19287400 29 88861408 22 89020330 12345866 45 19287401 28 88861420 18 89021329 <td>211955532524104549</td> | 211955532524104549 |
| 01052351 37 19259104 50 88861206 35 88886142 01052626 34 19370291 18 88861314 50 88900330 01052948 37 19260234 11 88861401 19 88900333 03634770 42 19260800 50 88861402 19 88900399 12301108 10 19260901 41 88861403 22 88900401 12302498 30 19286291 31 88861404 22 88900402 12344968 35 19286292 31 88861405 19 88901445 12345097 9 19286318 32 88861406 19 88901975 12345579 36 19286319 32 88861407 22 89020326 12345726 9 19287400 29 88861408 22 89020330 12345866 45 19287401 28 88861420 18 89021329 | 1952532524104549 |
| 01052626 34 19370291 18 88861314 50 88900330 01052948 37 19260234 11 88861401 19 88900333 03634770 42 19260800 50 88861402 19 88900399 12301108 10 19260901 41 88861403 22 88900401 12302498 30 19286291 31 88861404 22 88900402 12344968 35 19286292 31 88861405 19 88901445 12345097 9 19286318 32 88861406 19 88901975 12345579 36 19286319 32 88861407 22 89020326 12345726 9 19287400 29 88861408 22 89020330 12345866 45 19287401 28 88861420 18 89021329 | 25 52 25 25 24 10 45 49 |
| 01052948 37 19260234 11 88861401 19 88900333 03634770 42 19260800 50 88861402 19 88900399 12301108 10 19260901 41 88861403 22 88900401 12302498 30 19286291 31 88861404 22 88900402 12344968 35 19286292 31 88861405 19 88901445 12345097 9 19286318 32 88861406 19 88901975 12345579 36 19286319 32 88861407 22 89020326 12345726 9 19287400 29 88861408 22 89020330 12345866 45 19287401 28 88861420 18 89021329 | 52 25 24 10 45 49 |
| 03634770 42 19260800 50 88861402 19 88900399 12301108 10 19260901 41 88861403 22 88900401 12302498 30 19286291 31 88861404 22 88900402 12344968 35 19286292 31 88861405 19 88901445 12345097 9 19286318 32 88861406 19 88901975 12345579 36 19286319 32 88861407 22 89020326 12345726 9 19287400 29 88861408 22 89020330 12345866 45 19287401 28 88861420 18 89021329 | 53 25 24 10 45 49 |
| 12301108 10 19260901 41 88861403 22 88900401 12302498 30 19286291 31 88861404 22 88900402 12344968 35 19286292 31 88861405 19 88901445 12345097 9 19286318 32 88861406 19 88901975 12345579 36 19286319 32 88861407 22 89020326 12345726 9 19287400 29 88861408 22 89020330 12345866 45 19287401 28 88861420 18 89021329 | 25 24 10 45 49 8 |
| 12302498 30 19286291 31 88861404 22 88900402 12344968 35 19286292 31 88861405 19 88901445 12345097 9 19286318 32 88861406 19 88901975 12345579 36 19286319 32 88861407 22 89020326 12345726 9 19287400 29 88861408 22 89020330 12345866 45 19287401 28 88861420 18 89021329 | 24 10 45 49 8 |
| 12344968 35 19286292 31 88861405 19 88901445 12345097 9 19286318 32 88861406 19 88901975 12345579 36 19286319 32 88861407 22 89020326 12345726 9 19287400 29 88861408 22 89020330 12345866 45 19287401 28 88861420 18 89021329 | 10 45 49 8 |
| 12345097 | 45 49 8 |
| 12345579 36 19286319 32 88861407 22 89020326 12345726 9 19287400 29 88861408 22 89020330 12345866 45 19287401 28 88861420 18 89021329 | 49 8 |
| 12345726 | 8 |
| 1234586645 1928740128 8886142018 89021329 | |
| | ^ |
| | |
| 1234586745 | |
| 12345884 | |
| 1234599637 | |
| 1234624141 1930045725 8886169833 89021939 | |
| 1234629014 1930185036 8886171925 89021940 | |
| 1234639011 1930312339 8886180052 89021958 | |
| 1234639111 1930331039 8886195026 89022180 | |
| 1234666844 1930386051 8886218241 89022219 | |
| 1235615012 1931714013 8886247252 92184900 | |
| 1235615012 1932935538 8886247736 | |
| 1237128741 1932944845 8886258737 | |
| 1237138639 1932945045 8886262424 | |
| 1237790036 1933090547 8886262827 | |
| 1237790536 1933104426 8886262938 | |
| 12377914 | |
| 12377969 | |
| 12377979 | |
| 1237811216 1933221146 8886345837 1237813417 1933324910 8886349431 | |
| 1237813417 1933324940 8886349531 | |
| 1237817635 1933351046 8886389917 | |
| 1237819527 1933351147 8886402615 | |
| 1237825513 1933351249 8886412711 | |
| 1237839013 1933351348 8886415522 | |
| 1237839827 19333514 | |
| 1237839927 1935169438 8886431414 | |
| 1237845417 1935185952 8886434648 | |
| 1237846414 1935188240 8886453312 | |
| 1237846520 1935261951 8886455221 | |
| 1237847848 1935275924 8886521438 | |
| 1237847948 1935312628 8886521616 | |
| 1237850047 | |
| 1237851214 1935430643 8886521818 | |
| 1237851426 | |
| 1237851553 | |
| 12378521 | |
| 12378560 | |
| 1237856115 1935572546 8886523123 | |
| 1237856215 1935640838 8886523720 | |
| 1237856335 1936688042 8886559533 | |
| 12378566 | |

BLANK

Adhesion Promoter



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 4 oz. | 1 | 10-1023 | 19368179 |

PRODUCT DESCRIPTION AND FUNCTION:

Adhesion Promoter is a liquid adhesion promoter used to improve the adhesion of low surface and medium surface energy plastics such as thermoplastic olefins (TPO), thermoplastic urethanes (TPU), polypropylene, EPDM, PC, and acrylic. A fluorescent dye has been added so that primer coverage can be verified. Adhesion promoter is specifically formulated to be used with acrylic foam tapes for automotive applications. Because substrate formulations and surface energies may vary for these materials, each application should be tested for compatibility.

Instructions: The bonding surface should be clean and dry. Contaminated surfaces should be cleaned with an appropriate solvent such as isopropyl alcohol. Observe precautions for solvent handling. Shake well before using. Apply a thin, uniform coating of the Adhesion Promoter to the bonding surface, using the minimum amount that will fully coat the surface. A wet coating thickness of approximately 0.002 inch (0.5 mm) or less is recommended. Although drying times may vary due to temperature and/or humidity, a drying time of 30-90 seconds is typical of this thickness. The adhesion promoter should be dry before applying the tape. For best results, apply tape within one hour after applying the adhesion promoter. Be sure the primer surface remains free from contaminants prior to laminating the tape. For Professional Use Only. Not for Retail Sale.

PRODUCT FEATURES AND BENEFITS:

- Increases the adhesive bond strength between foam tapes and a variety of plastic polymers
- Designed for common applications, including, moldings, inserts, bumpers, and automotive fascia
- Multi-purpose product can also be used to prepare surfaces for the application of other adhesives

Glass Adhesion Promoter - Aerosol



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 11 oz. | 6 | 10-1011 | 12378555 |

PRODUCT DESCRIPTION AND FUNCTION:

This Glass Adhesion Promoter is specifically designed to treat and seal glass surfaces in preparation for bonding as well as adhere metal to glass. Windshields are the most common application for this product. It helps optimize and prolong adhesion to glass surfaces in certain applications where moisture and humidity is usually present. For Professional Use Only. Not for Retail Sale.

PRODUCT FEATURES AND BENEFITS:

- Product prevents moisture from interfering with the adhesion process, resulting in an improved long-term bond
- Designed to treat and seal glass surfaces in preparation for bonding
- Specially engineered to prepare surfaces for adhesion between metal and glass

High Strength-Slip Fit Retaining Compound



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 1.69 oz. | 1 | 10-1022 | 19333514 |

PRODUCT DESCRIPTION AND FUNCTION:

ACDelco High Strength-Slip Fit Retaining Compound is a single part, high viscosity, high strength anaerobic resin used for binding rigid assemblies of all types. This material can be used effectively to help increase the strength of most mechanical assemblies. It is not recommended for extremely close or interference fits.

Hot Melt Adhesive Sticks



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|--------------------------|--------------|---------------------|----------------|
| 14 - 17 1/2" x 12" stick | 1 | 10-1019 | 12377914 |

PRODUCT DESCRIPTION AND FUNCTION:

Hot Melt Adhesive Sticks are excellent for bonding a wide variety of surfaces. They are a high performance adhesive capable of bonding wood, metal, most plastics. For automotive application, this product bonds seat covers to foam cushions and is useful for reattaching vinyl trim. Hot Melt Adhesive Sticks meet the GM Specification for use in seat bonding.

- Designed with a polyamide composition that creates a long open time, the time where a surface retains enough tack to make a bond. The product is able to create a strong bond up to 75 seconds after initial application
- Has excellent resistance to plasticizer migration, which can lead to loss of flexibility, brittleness, and cracking
- Low application viscosity makes adhesive easy to apply



Instant Gel Adhesive

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| .07 oz. | 12 | 10-1020 | 19332001 |

PRODUCT DESCRIPTION AND FUNCTION:

This Instant Gel Adhesive is designed for the assembly of difficult-to-bond materials which require uniform stress distribution and strong tension and/or shear strength. The product provides rapid bonding of a wide range of materials, including metals, plastics and elastomers. The gel consistency prevents adhesive flow even on vertical surfaces. It is also suited for bonding porous materials such as wood, paper, leather and fabric.

WARNING: Cancer - www.P65Warnings.ca.gov.

Metal Patch Panel Adhesive



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 7.6 oz. | 1 | 10-1015 | 12378566 |

PRODUCT DESCRIPTION AND FUNCTION:

This product is a metal bonding adhesive used for patch panel bonding and bonding of dissimilar metals, cab corners, panel sections, and aluminum trailer repair patches.

For Professional Use Only. Not for Retail Sale.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

Plastic Installation Adhesive



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 10.10 oz. | 1 | 10-1013 | 89020330 |

PRODUCT DESCRIPTION AND FUNCTION:

This adhesive is a structural adhesive for bonding a variety of plastics-to-plastics and plastics to primed, painted, or e-coated metals. It can be used to bond plastic body panels, spoilers, and ground effects. It meets GM 6448G adhesion guidelines for bonding exterior sheet molding compound (SMC) for aftermarket service use. Product has no VOCs, 100% solids, and is resistant to extreme temperatures.

For Professional Use Only. Not for Retail Sale.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

Plastic Repair Adhesive (High-Strength)



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 1.7 oz. | 12 | 10-1014 | 88861039 |

PRODUCT DESCRIPTION AND FUNCTION:

Plastic Repair Adhesive (High-Strength) is an ideal high quality aftermarket replacement component for one or more of the following vehicle systems: engine mechanical, cooling, hvac, automatic transmission/transaxle, manual drivetrain and axles, brakes, steering and suspension, wiper and washer, and/or engine fuel management. This premium aftermarket compound is manufactured to meet or exceed your expectations for fit, form, and function. For Professional Use Only. Not for Retail Sale.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Rearview Mirror Adhesive



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| . 1 oz. | 12 | 10-1010 | 89021329 |

PRODUCT DESCRIPTION AND FUNCTION:

Rearview Mirror Adhesive is a two-part adhesive that permanently bonds mirror buttons to windshields. The product achieves handling strength in seconds, and mirror mounting strength in 30 minutes. ODC free. NOT designed for PLASTIC buttons.

Structural Bonding Epoxy - Cartridge (Two Parts: 6.4 oz. Resin/6.4 oz. Hardener)



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 6.4 oz. x 2 | 6 | 10-7015 | 12345726 |

PRODUCT DESCRIPTION AND FUNCTION:

This dual cartridge contains a two-part epoxy for structural bonding. Used with the dealer equipment group's body panel adhesive applicator gun on SMC, FRP, GTX, and other rigid plastic parts. Forms an initial bond in 40-50 minutes, full cures takes 24 hours. For Professional Use Only. Not for Retail Sale.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

PRODUCT FEATURES AND BENEFITS:

Designed for use on Corvette and U-Van panels.

Structural Metal Bonding Adhesive



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 7.6 oz. | 6 | 10-1016 | 12378567 |

PRODUCT DESCRIPTION AND FUNCTION:

This product contains glass beads that create a bond like thickness, regardless of clamping techniques. It provides corrosion protection, bonds to bare metal without the need for primers. It has a built-in color indicator that turns from dark gray to green as adhesive cures. Applicator tool is required for applications.

For Professional Use Only. Not for Retail Sale.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

PRODUCT FEATURES AND BENEFITS:

· Applicator 285-LRD-301 is available through Kent-Moore.

Structural Urethane Installation Adhesive



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 1.7 oz. | 12 | 10-1012 | 12378568 |

PRODUCT DESCRIPTION AND FUNCTION:


This Structural Urethane Installation Adhesive is a high-strength structural adhesive that is used for bonding a variety of plastics to other plastics (e.g. SMC, fiberglass, and carbon fiber) and plastics to primed, painted, or e-coated metals. This urethane adhesive is engineered with a non-sag urethane formula. Requires the use of a dispensing tool that is not included.

For Professional Use Only. Not for Retail Sale.

PRODUCT FEATURES AND BENEFITS:

- Effective for general purpose bonding of trim components and small body panels, including, spoilers, ground effects, headlight buckets
- Provides faster cure time for smaller body panels
- · Adhesive curing can be accelerated by heat

Tape



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| Kit (2 pieces) | 1 | N/A | 19299353 |

PRODUCT DESCRIPTION AND FUNCTION:

Tape used to secure the active noise cancellation microphones to the truck's headliner.

Weather Strip Adhesive Gel - Black



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 5 oz. | 12 | 10-1007 | 12345097 |

PRODUCT DESCRIPTION AND FUNCTION:

This Weather Strip Adhesive Gel is a black cement that bonds rubber weather-stripping to rubber, metal, or painted surfaces. Product is resistant to gasoline, kerosene, antifreeze, and other solvents. Will also withstand vibration and extreme temperature changes. WARNING: Reproductive Harm - www.P65Warnings.ca.gov.

Air Conditioner Compressor Oil PAG-SPA2 (R-1234yf)



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 8 fl. oz. | 6 | 10-4106 | 19333249 |

PRODUCT DESCRIPTION AND FUNCTION:

Air Conditioning Compressor Oil is formulated with special synthetic PolyAlkylene Glycol (PAG) oils and various additives to provide excellent performance for automobile air conditioner systems. The detailed Directions for Use is included inside the Kent Moore kit case.

- This product must be used for R-1234yf A/C systems approved to GM Specification 9986364
- To be used with Kent Moore A/C Oil Injection Kit J-45037
- Refer to Direction for Use in J-45037

For Professional Use Only. Not for Retail Sale.

Air Conditioner Compressor Oil



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 8 oz. | 6 | 10-4112 | 19354657 |

PRODUCT DESCRIPTION AND FUNCTION:

Air Conditioner Compressor Oil (Universal R-1234yf) is a fully formulated ISO VG46 grade polyalkylene glycol (PAG) lubricant designed specifically for GM belt driven air conditioner compressor applications with HFO R-1234yf refrigerant. This product should NOT be used with GM electric air conditioner compressors. Always refer to the service manual for the latest service information.

- This product must be used for R-1234yf air conditioning systems
- approved to GM Specification 9986479.
- To be used with A/C Oil Injection Kit J-45037.
- Refer to Direction for Use in J-45037.

For Professional Use Only. Not for Retail Sale.

Air Conditioning Compressor Oil (46 Viscosity) - Cartridge



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 8 oz. | 6 | 10-5026 | 88901445 |

PRODUCT DESCRIPTION AND FUNCTION:

This fully synthetic Air Conditioning Compressor Oils (46 Viscosity) is formulated to provide unsurpassed lubricity, wear protection, and proper miscibility with ozone-friendly refrigerants like R-134a (except for R4 and A6 systems), as well as R-12 in the case of retrofits. Formulated for automotive air conditioning systems, Air Conditioning Compressor Oil (46 Viscosity) has excellent chemical, thermal, and hydrolytic stability.

For Professional Use Only. Not for Retail Sale.

PRODUCT FEATURES AND BENEFITS:

- Fully synthetic compressor oil specially formulated for lubricity and wear protection
- Chemically engineered for miscibility with ozone-friendly refrigerants
- High-quality formula designed for chemical, thermal, and hydrolytic stability

Air Conditioning Compressor Oil (525 Viscosity)



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|-----------------------|
| 32 oz. | 12 | 15-117 | 12301108 |

PRODUCT DESCRIPTION AND FUNCTION:

Air Conditioning Compressor Oil is a 525 SAE mineral oil universal for all R-12 systems.

For Professional Use Only. Not for Retail Sale.

Air Conditioning Oil POE



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|-----------------------|
| 3.5 oz. | 6 | 10-4075 | 88862657 |

PRODUCT DESCRIPTION AND FUNCTION:

Air Conditioning Oil Polyolester (POE) is a low moisture, synthetic, compressor oil. It is designed for use with electric two-mode Hybrid air conditioning units (RPO HP2) or for use on 2008-2011 General Motors C/K Pickup and Utility trucks. The cartridge comes sealed in a foil bag to prevent excess moisture and contamination. Air Conditioning Oil POE requires the use of an applicator tool that is not included.

For Professional Use Only. Not for Retail Sale.

- Low moisture, synthetic formula to meet system needs
- Sealed foil packaging to help protect against contamination prior to application
- High-quality formula to help keep your air conditioning system running smoothly

Air Conditioning (A/C) System Dye



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| .25 oz. | 12 | 10-5072 | 88864127 |

PRODUCT DESCRIPTION AND FUNCTION:

Air Conditioning (A/C) System Dye is designed to help locate refrigerant leaks within GM mobile air conditioning systems. It is for use in R-134a and R-1234yf refrigerant systems using Polyalkylene glycol (PAG) or Polyolester (POE) lubricants.

Use with tool 12344968.

For Professional Use Only. Not for Retail Sale.

PRODUCT FEATURES AND BENEFITS:

- Designed to quickly pinpoint leaks in R-12 mineral oil air conditioning systems
- Remains safely in the air conditioning system for future leak detection
- Premeasured dose for one-time easy-use application

Cooling Coil Coating Applicator Kit



Container Size Unit Package ACDelco Part Number GM Part Number Kit 1 10-5052 12346391

PRODUCT DESCRIPTION AND FUNCTION:

The Cooling Coil Coating Applicator Kit comes with a non-aerosol bottle of cooling coil coating and one Ulti-Flex applicator tool. The coating's formula covers your air conditioning evaporator with a thin, acrylic coating that helps surfaces to shed odor-causing moisture quickly and improves air conditioning efficiency.

For Professional Use Only. Not for Retail Sale.

PRODUCT FEATURES AND BENEFITS:

- Kit includes an Ulti-Flex Applicator tool that bends to fit any configuration and has a precision atomizing tip which assures proper cooling coil coating diffusion
- Solution can be quickly applied in just 20 minutes and the vehicle can be back on the road within an hour
- · Acrylic coating helps protect against unwanted odor

Cooling Coil Coating - Refill for Applicator Kit



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 4 oz. | 2 | 10-5051 | 12346390 |

PRODUCT DESCRIPTION AND FUNCTION:

The non-aerosol bottle of Cooling Coil Coating is a refill for cooling coil coating originally sold with the Cooling Coil Coating Applicator Kit (Tool). It improves air conditioning efficiency by covering your air conditioning evaporator with a thin, acrylic coating that helps surfaces to shed odor-causing moisture quickly.

For Professional Use Only. Not for Retail Sale.

PRODUCT FEATURES AND BENEFITS:

- Exact replacement for the solution sold with the Cooling Coil Coating Applicator Kit
- Solution can be quickly applied in just 20 minutes and the vehicle can be back on the road within an hour
- Acrylic coating helps protect against unwanted odor

R-1234yf Refrigerant



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 4.5 kg. | 1 | 19260234 | 19260234 |

PRODUCT DESCRIPTION AND FUNCTION:

R-134a Refrigerant is used for current air conditioning systems and a retrofit fluid for older systems. It is made specifically for use in vehicles equipped with an R-134a refrigerant system.

For Professional Use Only. Not for Retail Sale.

PRODUCT FEATURES AND BENEFITS:

- The non-ozone depleting gas is more environmentally friendly than R-12 refrigerants
- High-quality formula to help keep your air conditioning system running smoothly
- Meets SAE J2776 purity standard meaning that the refrigerant contains limited number of unsaturated impurities or that there is a lower likelihood of the product containing contaminants that can contribute to the formation of sludge or tar in the cooling system

R-134a Refrigerant



| • | | | |
|----------------|--------------|----------------------------|----------------|
| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
| 12 oz. | 12 | 10-9255 | 19355335 |

PRODUCT DESCRIPTION AND FUNCTION:

For Professional Use Only. Not for Retail Sale.

R-134a Refrigerant is used for current air conditioning systems and a retrofit fluid for older systems. It is made specifically for use in vehicles equipped with an R-134a refrigerant system.

Instructions: DO NOT CONNECT CAN TO THE HIGH-PRESSURE SIDE OF SYSTEM OR ANY SYSTEM WITH A PRESSURE HIGHER THAN 170 PSIG. This may cause can to burst, resulting in severe injury. Start engine and set air conditioner controls for maximum cooling. Check system with gauge to determine low pressure (suction) service port. Charge system only through low pressure side. Hold can upright to charge gas. While charging, rotate can between 12 o'clock and 3 o'clock every 2 to 3 seconds while continually agitating (shaking) the can back and forth. Continue this process until the can is empty (5 to 15 minutes) or until the correct amount of refrigerant is charged into the air conditioning system. Always store partially filled cans with recharge hose attached. Use only the required amount. USE ONLY WITH SYNTHETIC OIL.

- The non-ozone depleting gas is more environmentally friendly than R-12 refrigerants
- High-quality formula to help keep your air conditioning system running smoothly
- Meets SAE J2776 purity standard meaning that the refrigerant contains limited number of unsaturated impurities or that there is a lower likelihood of the product containing contaminants that can contribute to the formation of sludge or tar in the cooling system





| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 30 lbs. | 1 | 15-119 | 12356150 |

PRODUCT DESCRIPTION AND FUNCTION:

R-134a Refrigerant is used for current air conditioning systems and a retrofit fluid for older systems. It is made specifically for use in vehicles equipped with an R-134a refrigerant system.

For Professional Use Only. Not for Retail Sale.

PRODUCT FEATURES AND BENEFITS:

- The non-ozone depleting gas is more environmentally friendly than R-12 refrigerants
- High-quality formula to help keep your air conditioning system running smoothly
- Meets SAE J2776 purity standard meaning that the refrigerant contains limited number of unsaturated impurities or that there is a lower likelihood of the product containing contaminants that can contribute to the formation of sludge or tar in the cooling system

R-134a Refrigerant



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|-------------------|---------------------|----------------|
| 30 lbs. | Pallet (40 units) | 15-119A | 88864533 |

PRODUCT DESCRIPTION AND FUNCTION:

R-134a Refrigerant is used for current air conditioning systems and a retrofit fluid for older systems. It is made specifically for use in vehicles equipped with an R-134a refrigerant system.

For Professional Use Only. Not for Retail Sale.

PRODUCT FEATURES AND BENEFITS:

- The non-ozone depleting gas is more environmentally friendly than R-12 refrigerants
- High-quality formula to help keep your air conditioning system running smoothly
- Meets SAE J2776 purity standard meaning that the refrigerant contains limited number of unsaturated impurities or that there is a lower likelihood of the product containing contaminants that can contribute to the formation of sludge or tar in the cooling system

Refrigerant Oil (150 Viscosity)



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 16 oz. | 12 | 15-118 | 12356151 |

PRODUCT DESCRIPTION AND FUNCTION:

Refrigerant Oil (150 Viscosity) is intended for use on R4 and A6 compressors within R-134a refrigerant systems. This product must be used for GM-Harrison manufactured compressors using R-134a refrigerant oil.

- Specially formulated for use in R4 and A6 compressors in R-134a refrigerant systems
- Approved for use in GM-Harrison manufactured compressors using R-134a refrigerant oil
- High-quality formula to help keep your air conditioning system running smoothly

Cooling System Seal Tabs





PRODUCT DESCRIPTION AND FUNCTION:

Cooling System Seal Tabs are designed with a non-toxic organic formula for use in radiator systems to seal and prevent leaks due to casting porosity in engine components. The tabs dissolve to lubricate internal components and seal coolant leaks. Cooling System Seal Tabs also inhibit the formation of rust and scale, neutralize pH imbalances, and control electrolysis. Consult the owner's manual for coolant system volume. Use 1.0g to 1.5g of sealant for each quart of coolant system volume.

PRODUCT FEATURES AND BENEFITS:

- Professional strength formula creates a permanent seal against minor or microscopic leaks and porosity
- The compatible seals work with water and all types of antifreeze including: conventional green or blue (silicate based), Extended Life red/orange, DEX-COOL, and yellow coolants
- Tabs are designed to be harmless to all plastic, metal, aluminum, hoses, and connections within the cooling system and will not add premature wear to cooling system components

CE Extended Life (Blue) Prediluted Antifreeze/Coolant



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|-----------------------|
| 1 gal. | 6 | 10-5071 | 19317140 |

PRODUCT DESCRIPTION AND FUNCTION:

CE Extended Life (Blue) Prediluted Antifreeze/Coolant is an advanced formula ethylene glycol based product that uses state of the art technology. This product contains no amines, no silicates, which may harm water pump seals, or borates, that may cause aluminum corrosion and pitting. CE Extended Life (Blue) Prediluted Antifreeze/Coolant provides long lasting protection for aluminum, cast iron, and all other engine components. THERE IS NO NEED TO ADD WATER. DO NOT MIX WITH ANY OTHER COLOR OR SPECIFICATION OF ANTIFREEZE/COOLANT.

WARNING: Reproductive Harm - www.P65Warnings.ca.gov.

PRODUCT FEATURES AND BENEFITS:

 When disposing of used antifreeze/coolant, follow local laws and regulations. If required, dispose at facilities licensed to accept household hazardous waste. If permitted, dispose in sanitary sewer system. Do not discard into storm sewers, septic systems, or onto the ground.

DEX-COOL® 50/50 Premix



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|---------------------------|---------------------|----------------|
| 1 gal. | 6 (24 unit minimum order) | 10-5027 | 12378390 |

PRODUCT DESCRIPTION AND FUNCTION:

Dex-Cool® 50/50 Premix is an orange, silicate and phosphate free, premium-grade coolant with a chemical composition that reduces breakdown of metal components in contact with the fluid. Based on carboxylate technology, Dex-Cool 50/50 Premix has the properties needed to optimize the efficiencies of the new hybrid vehicles. This product is acceptable for use in all vehicles that require Dex-Cool coolant. Perfect for on the go situations, Dex-Cool 50/50 Premix comes pre-diluted with specially filtered water and is ready for instant use.

WARNING: Reproductive Harm - www.P65Warnings.ca.gov.

PRODUCT FEATURES AND BENEFITS:

- Specially formulated for long service intervals, the coolant can last up to 5 years or 150,000 miles. (Maintenance needs vary with different uses and driving conditions. See your Owner's Manual for more information)
- Provides effective long-term anti-corrosion support by protecting brass, cast iron, steel, solder, and copper components. Also provides superior high-temperature protection for aluminum components
- Non-silicate formula retains excellent heat transfer characteristics for improved water pump life

DEX-COOL® 50/50 Premix



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 1 gal. | 216 (Pallet) | N/A | 88864312 |

PRODUCT DESCRIPTION AND FUNCTION:

Dex-Cool 50/50 Premix is an orange, silicate and phosphate free, premium-grade coolant with a chemical composition that reduces breakdown of metal components in contact with the fluid. Based on carboxylate technology, Dex-Cool 50/50 Premix has the properties needed to optimize the efficiencies of the new hybrid vehicles. This product is acceptable for use in all vehicles that require Dex-Cool coolant. Perfect for on-the-go situations, Dex-Cool 50/50 Premix comes pre-diluted with specially filtered water and is ready for instant

WARNING: Reproductive Harm - www.P65Warnings.ca.gov.

- Specially formulated for long service intervals, the coolant can last up to 5 years or 150,000 miles. Maintenance needs vary with different uses and driving conditions. Refer to Owner's Manual for more information.
- Provides effective long-term anti-corrosion support by protecting brass, cast iron, steel, solder, and copper components. Also provides superior high-temperature protection for aluminum components.
- Non-Silicate formula retains excellent heat transfer characteristics for improved water pump life.

DEX-COOL® 50/50 Premix



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 55 gal. drum | 1 | 10-5038 | 88864314 |

PRODUCT DESCRIPTION AND FUNCTION:

Dex-Cool® 50/50 Premix is an orange, silicate and phosphate free, premium-grade coolant with a chemical composition that reduces breakdown of metal components in contact with the fluid. Based on carboxylate technology, Dex-Cool 50/50 Premix has the properties needed to optimize the efficiencies of the new hybrid vehicles. This product is acceptable for use in all vehicles that require Dex-Cool coolant. Perfect for on the go situations, Dex-Cool 50/50 Premix comes pre-diluted with specially filtered water and is ready for instant use.

For Professional Use Only. Not for Retail Sale. WARNING: Reproductive Harm - www.P65Warnings.ca.gov.

PRODUCT FEATURES AND BENEFITS:

- Specially formulated for long service intervals, the coolant can last up to 5 years or 150,000 miles. (Maintenance needs vary with different uses and driving conditions. See your Owner's Manual for more information)
- Provides effective long-term anti-corrosion support by protecting brass, cast iron, steel, solder, and copper components. Also provides superior high-temperature protection for aluminum components
- Non-silicate formula retains excellent heat transfer characteristics for improved water pump life

DEX-COOL® Concentrate



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|---------------------------|---------------------|----------------|
| 1 gal. | 6 (24 unit minimum order) | 10-101 | 12346290 |

PRODUCT DESCRIPTION AND FUNCTION:

Dex-Cool® Extended Life is an orange, silicate and phosphate free, premium-grade coolant/antifreeze that is formulated with a chemical composition that reduces breakdown of metal components in contact with the fluid. Based on carboxylate technology, Dex-Cool Extended Life has the properties needed to optimize the efficiencies of the new hybrid vehicles. This product is acceptable for use in all vehicles that require Dex-Cool coolant and the undiluted formula means that the user can customize the concentrations of water to coolant/antifreeze for optimum performance in a range of environments.

WARNING: Reproductive Harm - www.P65Warnings.ca.gov.

PRODUCT FEATURES AND BENEFITS:

- Specially formulated for long service intervals, the coolant can last up to 5 years or 150,000 miles. (Maintenance needs vary with different uses and driving conditions. See your Owner's Manual for more information)
- Provides effective long-term anti-corrosion support by protecting brass, cast iron, steel, solder, and copper components. Also provides superior high-temperature protection for aluminum components
- Non-silicate formula retains excellent heat transfer characteristics for improved water pump life

DEX-COOL® Concentrate



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 1 gal. | 216 (Pallet) | N/A | 12378464 |

PRODUCT DESCRIPTION AND FUNCTION:

Dex-Cool® Extended Life is an orange, silicate and phosphate free, premium-grade coolant/antifreeze that is formulated with a chemical composition that reduces breakdown of metal components in contact with the fluid. Based on carboxylate technology, Dex-Cool Extended Life has the properties needed to optimize the efficiencies of the new hybrid vehicles. This product is acceptable for use in all vehicles that require Dex-Cool coolant and the undiluted formula means that the user can customize the concentrations of water to coolant/antifreeze for optimum performance in a range of environments.

WARNING: Reproductive Harm - www.P65Warnings.ca.gov.

PRODUCT FEATURES AND BENEFITS:

- Specially formulated for long service intervals, the coolant can last up to 5 years or 150,000 miles. (Maintenance needs vary with different uses and driving conditions. See your Owner's Manual for more information)
- Provides effective long-term anti-corrosion support by protecting brass, cast iron, steel, solder, and copper components. Also provides superior high-temperature protection for aluminum components
- Non-silicate formula retains excellent heat transfer characteristics for improved water pump life

DEX-COOL® Concentrate



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 55 gal. drum | 1 | 10-125 | 12378512 |

PRODUCT DESCRIPTION AND FUNCTION:

Dex-Cool® Extended Life is an orange, silicate and phosphate free, premium-grade coolant/antifreeze that is formulated with a chemical composition that reduces breakdown of metal components in contact with the fluid. Based on carboxylate technology, Dex-Cool Extended Life has the properties needed to optimize the efficiencies of the new hybrid vehicles. This product is acceptable for use in all vehicles that require Dex-Cool coolant and the undiluted formula means that the user can customize the concentrations of water to coolant/antifreeze for optimum performance in a range of environments. For Professional Use Only. Not for Retail Sale.

WARNING: Reproductive Harm - www.P65Warnings.ca.gov.

- Specially formulated for long service intervals, the coolant can last up to 5 years or 150,000 miles. (Maintenance needs vary with different uses and driving conditions. See your Owner's Manual for more information)
- Provides effective long-term anti-corrosion support by protecting brass, cast iron, steel, solder, and copper components. Also provides superior high-temperature protection for aluminum components
- Non-silicate formula retains excellent heat transfer characteristics for improved water pump life

Radiator Fast Flush + Cleaner



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 22 oz. | 6 | 10-5070 | 88864026 |

PRODUCT DESCRIPTION AND FUNCTION:

Where need is indicated by GM service bulletins to remove corrosion or for customer complaints of coolant and/or hose odor, the citrus based product can be applied. Application takes only 10 minutes. For neglected cooling systems it may be necessary to repeat application and to run the engine for a longer time period.

Traditional Coolant Concentrate



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|---------------------------|---------------------|----------------|
| 1 gal. | 6 (24 unit minimum order) | 10-5034 | 12378560 |

PRODUCT DESCRIPTION AND FUNCTION:

Traditional (Universal) 'Yellow' Coolant is a high-boiling, non-evaporating, silicate free and phosphate free coolant/antifreeze that contains additional chemical components to protect against rust and corrosion. It can be used with low- or high-opening thermostats, at high altitudes, with diesel applications when Supplemental Coolant Additives (SCAs) are used, and vehicles where a long life coolant/ antifreeze is wanted EXCEPT medium duty trucks. Vehicles that use Dex-cool and are still under warranty cannot use this product and maintain warranty coverage. Traditional (Universal) 'Yellow' Coolant Concentrate mixes perfectly with water, flows freely, and transfers heat efficiently while protecting your engines aluminum components. The undiluted formula of Traditional (Universal) 'Yellow' Coolant Concentrate means that the user can customize the concentrations of water to coolant for optimum performance in a range of environments. WARNING: Reproductive Harm - www.P65Warnings.ca.gov.

PRODUCT FEATURES AND BENEFITS:

- High quality design includes excellent heat transfer properties, anti-foam characteristics, and corrosion protection for aluminum, brass, copper, solder and cast iron)
- Nitrite, amine, and borax-free design is environmentally friendly
- Compatible formula can be used with most cooling system filters and other conventional brands of coolant

Traditional Coolant Concentrate



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------------|---------------------|-----------------------|
| 1 gal. | 216 units (pallet) | N/A | 12378562 |

PRODUCT DESCRIPTION AND FUNCTION:

Traditional (Universal) 'Yellow' Coolant is a high-boiling, non-evaporating, silicate free and phosphate free coolant/antifreeze that contains additional chemical components to protect against rust and corrosion. It can be used with low- or high-opening thermostats, at high altitudes, with diesel applications when Supplemental Coolant Additives (SCAs) are used, and vehicles where a long life coolant/antifreeze is wanted EXCEPT medium duty trucks. Vehicles that use Dex-cool and are still under warranty cannot use this product and maintain warranty coverage. Traditional (Universal) 'Yellow' Coolant Concentrate mixes perfectly with water, flows freely, and transfers heat efficiently while protecting your engines aluminum components. The undiluted formula of Traditional (Universal) 'Yellow' Coolant Concentrate means that the user can customize the concentrations of water to coolant for optimum performance in a range of environments. WARNING: Reproductive Harm - www.P65Warnings.ca.gov.

PRODUCT FEATURES AND BENEFITS:

- High quality design includes excellent heat transfer properties, anti-foam characteristics, and corrosion protection for aluminum, brass, copper, solder and cast iron)
- Nitrite, amine, and borax-free design is environmentally friendly
- Compatible formula can be used with most cooling system filters and other conventional brands of coolant

Traditional Coolant Concentrate



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 55 gal. drum | 1 | 10-5032 | 12378561 |

PRODUCT DESCRIPTION AND FUNCTION:

Traditional (Universal) 'Yellow' Coolant is a high-boiling, non-evaporating, silicate free and phosphate free coolant/antifreeze that contains additional chemical components to protect against rust and corrosion. It can be used with low- or high-opening thermostats, at high altitudes, with diesel applications when Supplemental Coolant Additives (SCAs) are used, and vehicles where a long life coolant/ antifreeze is wanted EXCEPT medium duty trucks. Vehicles that use Dex-cool and are still under warranty cannot use this product and maintain warranty coverage. Traditional (Universal) 'Yellow' Coolant Concentrate mixes perfectly with water, flows freely, and transfers heat efficiently while protecting your engines aluminum components. The undiluted formula of Traditional (Universal) 'Yellow' Coolant Concentrate means that the user can customize the concentrations of water to coolant for optimum performance in a range of environments. For Professional Use Only. Not for Retail Sale. WARNING: Reproductive Harm - www.P65Warnings.ca.gov.

- High quality design includes excellent heat transfer properties, anti-foam characteristics, and corrosion protection for aluminum, brass, copper, solder and cast iron)
- Nitrite, amine, and borax-free design is environmentally friendly
- Compatible formula can be used with most cooling system filters and other conventional brands of coolant



Car Wash Shampoo

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 5 gal. | 1 | 10-8042 | 88865216 |

PRODUCT DESCRIPTION AND FUNCTION:

Car Wash Shampoo is a premium wash and gloss enhancer shampoo in one. It is tough on dirt, yet gentle on paint and will not remove wax or other surface protectants. This product creates long-lasting suds and foam for a full, detailed cleaning of your vehicle's exterior. For Professional Use Only. Not for Retail Sale.

Product is not available for sale in the State of California. Must be compliant to C.A. S.B. 258.

PRODUCT FEATURES AND BENEFITS:

- Formulated with synthetic polymers to loosen and emulsify the toughest dirt and road grime
- pH balanced with free-rinsing conditioning agents and paint nutrients, to clean and nourish vehicle's finish while providing sparkling, streak and spot-free results
- Scientifically formulated with lubricating properties to be gentle on all paint finishes as well as rubber, vinyl, and plastic components

Car Wash Shampoo



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 16 oz. | 6 | 10-8043 | 88865217 |

PRODUCT DESCRIPTION AND FUNCTION:

Car Wash Shampoo is a premium wash and gloss enhancer shampoo in one. It is tough on dirt, yet gentle on paint and will not remove wax or other surface protectants. This product creates long-lasting suds and foam for a full, detailed cleaning of your vehicle's exterior. Product is not available for sale in the State of California. Must be compliant to C.A. S.B. 258.

PRODUCT FEATURES AND BENEFITS:

- Formulated with synthetic polymers to loosen and emulsify the toughest dirt and road grime
- pH balanced with free-rinsing conditioning agents and paint nutrients, to clean and nourish vehicle's finish while providing sparkling, streak and spot-free results
- Scientifically formulated with lubricating properties to be gentle on all paint finishes as well as rubber, vinyl, and plastic components

Car Wash Shampoo



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 4 oz. | 30 | 10-8044 | 88865228 |

PRODUCT DESCRIPTION AND FUNCTION:

Car Wash Shampoo is a premium wash and gloss enhancer shampoo in one. It is tough on dirt, yet gentle on paint and will not remove wax or other surface protectants. This product creates long-lasting suds and foam for a full, detailed cleaning of your vehicle's exterior. Product is not available for sale in the State of California. Must be compliant to C.A. S.B. 258.

PRODUCT FEATURES AND BENEFITS:

- Formulated with synthetic polymers to loosen and emulsify the toughest dirt and road grime
- pH balanced with free-rinsing conditioning agents and paint nutrients, to clean and nourish vehicle's finish while providing sparkling, streak and spot-free results
- Scientifically formulated with lubricating properties to be gentle on all paint finishes as well as rubber, vinyl, and plastic components

Chevrolet Vehicle Care Kit



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| Large | 1 | 12378136 | 12378136 |

PRODUCT DESCRIPTION AND FUNCTION:

The Chevrolet Vehicle Care kit contains the following appearance products:

88865217 - Car Wash Shampoo - 16 oz.

88865218 - Cleaner Wax - 16 oz.

88865219 - Quick Detailer - 16 oz.

88865237 - Ultra Fine Microfiber Towel (15" x 15")

Product is not available for sale in the State of California. Must be compliant to C.A. S.B. 258.

PRODUCT FEATURES AND BENEFITS:

 GM reserves the right to discontinue/change any product in this kit for a product of similar price without notice.

Corvette Vehicle Care Kit



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| Large | 1 | 12378112 | 12378112 |

PRODUCT DESCRIPTION AND FUNCTION:

The Corvette Vehicle Care kit contains the following appearance products:

88865217 - Car Wash Shampoo - 16 oz.

88865218 - Cleaner Wax - 16 oz.

88865219 - Quick Detailer - 16 oz.

88865237 - Ultra Fine Microfiber Towel (15" x 15")

Product is not available for sale in the State of California. Must be compliant to C.A. S.B. 258.

PRODUCT FEATURES AND BENEFITS:

 GM reserves the right to discontinue/change any product in this kit for a product of similar price without notice.

GM Vehicle Care Kit



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| Large | 1 | 88863899 | 88863899 |

PRODUCT DESCRIPTION AND FUNCTION:

The GM Vehicle Care kit contains the following appearance products:

88861405 - Leather, Vinyl and Plastic Cleaner - 8 oz.

88861406 - Leather and Vinyl Conditioner - 8 oz.

88861407 - Upholstery/Carpet Stain Remover - Gold Formula - 8 oz. 88861408 - Upholstery/Carpet Stain Remover - Red Formula - 8 oz.

88865237 - Ultra Fine Microfiber Towel (15" x 15")

Product is not available for sale in the State of California. Must be

compliant to C.A. S.B. 258.

PRODUCT FEATURES AND BENEFITS:

• GM reserves the right to discontinue/change any product in this kit for a product of similar price without notice.

GM Vehicle Care Kit



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| Small | 12 | 12378454 | 12378454 |

PRODUCT DESCRIPTION AND FUNCTION:

The GM Vehicle Care kit contains the following appearance products:

19370291 - Glass Cleaner - 6 oz.

88865228 - Car Wash Shampoo - 4 oz.

88865229 - Cleaner Wax - 4 oz.

88865231 - Vinyl, Rubber and Tire Dressing - 4 oz.

88865237 - Ultra Fine Microfiber Towel (15" x 15")

Product is not available for sale in the State of California. Must be compliant to C.A. S.B. 258.

PRODUCT FEATURES AND BENEFITS:

• GM reserves the right to discontinue/change any product in this kit for a product of similar price without notice.

GMC Vehicle Care Kit



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|-----------------------|
| Large | 1 | 12378134 | 12378134 |

PRODUCT DESCRIPTION AND FUNCTION:

The GMC Vehicle Care kit contains the following

appearance products:

88865217 - Car Wash Shampoo - 16 oz.

88865218 - Cleaner Wax - 16 oz. 88865219 - Quick Detailer - 16 oz.

88865237 - Ultra Fine Microfiber Towel (15" x 15")

Product is not available for sale in the State of California. Must be

compliant to C.A. S.B. 258.

PRODUCT FEATURES AND BENEFITS:

• GM reserves the right to discontinue/change any product in this kit for a product of similar price without notice.

Cleaner Wax



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 16 oz. | 6 | 10-8045 | 88865218 |

PRODUCT DESCRIPTION AND FUNCTION:

Cleaner Wax is manufactured from the highest quality raw materials to deliver a superior product. This treatment is a 100% pure carnauba-based wax and polish formulated to clean, shine, restore, and protect paint in one easy step. Cleaner Wax adds gloss and depth to your vehicle's finish without leaving behind powdery residue. Its non-smear formula is safe for all finishes, including clear coat.

Product is not available for sale in the State of California. Must be compliant to C.A. S.B. 258.

PRODUCT FEATURES AND BENEFITS:

- Uses new molecular-chemistry formulas with UV (40) sunscreen protection to create a long lasting wet-look shine, improve resistance to degenerative environmental elements, and easily remove fine paint defects, tree sap, water spots, bug/bird marks, and other environmental and industrial fallout
- Treatment bonds and wipes off in seconds to deliver an effortless, crystal clear, high-gloss finish
- Multi-surface product for a variety of vehicles that can be used on glass, stainless steel, fiberglass, chrome, and carbon graphite, and is safe for use on cars, trucks, planes, boats, motorcycles, and RVs

Cleaner Wax



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 4 oz. | 30 | 10-8046 | 88865229 |

PRODUCT DESCRIPTION AND FUNCTION:

Cleaner Wax is manufactured from the highest quality raw materials to deliver a superior product. This treatment is a 100% pure carnauba-based wax and polish formulated to clean, shine, restore, and protect paint in one easy step. Cleaner Wax adds gloss and depth to your vehicle's finish without leaving behind powdery residue. Its non-smear formula is safe for all finishes, including clear coat.

Product is not available for sale in the State of California. Must be compliant to C.A. S.B. 258.

PRODUCT FEATURES AND BENEFITS:

- Uses new molecular-chemistry formulas with UV (40) sunscreen protection to create a long lasting wet-look shine, improve resistance to degenerative environmental elements, and easily remove fine paint defects, tree sap, water spots, bug/bird marks, and other environmental and industrial fallout
- Treatment bonds and wipes off in seconds to deliver an effortless, crystal clear, high-gloss finish
- Multi-surface product for a variety of vehicles that can be used on glass, stainless steel, fiberglass, chrome, and carbon graphite, and is safe for use on cars, trucks, planes, boats, motorcycles, and RVs

Cloth/Carpet Cleaner Concentrate



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 67.6 oz. | 4 | 10-8025 | 88861420 |

PRODUCT DESCRIPTION AND FUNCTION:

Cloth/Carpet Cleaner Concentrate effectively removes the most difficult-to-clean stains from upholstery, carpet, and other fabrics. This cloth/carpet cleaner is specially formulated for automotive application and can be used to remove dirt, grease, and grime in all vehicles. Product is not available for sale in the State of California. Must be compliant to C.A. S.B. 258.

PRODUCT FEATURES AND BENEFITS:

- Slightly acidic engineered with lower pH levels helps to remove soap and alkalinity from fabric surfaces (often left behind by using improper, soapy solutions)
- 32:1 ratio (4 oz. of concentrate per 1 gallon of water) makes it easy to prepare large amounts of cleaning solution
- Can be used along with a heavy-duty extractor to clean large areas and/or heavily soiled fabrics

Glass Cleaner - Aerosol



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 6 oz. | 12 | 10-8035 | 19370291 |

PRODUCT DESCRIPTION AND FUNCTION:

Glass Cleaner is specially formulated for cleaning windows on automobiles, trucks, airplanes, and boats. It can also double as a household window and glass cleaner. This product is a foamy, non-streaking cleaner that can eliminate the toughest contaminants from glass surfaces. WARNING: Reproductive Harm - www.P65Warnings.ca.gov.

PRODUCT FEATURES AND BENEFITS:

- Specially designed to quickly and effectively removes dirt, grime, cigarette smoke, fingerprints, and other contaminants from glass surfaces
- Versatile glass cleaner created for use on automotive windows, but can also be used as a household window and glass cleaner
- · Quality formula is foamy and non-streaking

Glass Cleaner - Aerosol



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 18 oz. | 12 | 10-8016 | 19370290 |

PRODUCT DESCRIPTION AND FUNCTION:

Glass Cleaner is specially formulated for cleaning windows on automobiles, trucks, airplanes, and boats. It can also double as a household window and glass cleaner. This product is a foamy, non-streaking cleaner that can eliminate the toughest contaminants from glass surfaces. SW to confirm P65 Substance

WARNING: Reproductive Harm - www.P65Warnings.ca.gov.

- Specially designed to quickly and effectively removes dirt, grime, cigarette smoke, fingerprints, and other contaminants from glass surfaces
- Versatile glass cleaner created for use on automotive windows, but can also be used as a household window and glass cleaner
- Quality formula is foamy and non-streaking

Interior Cleaner Brush



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 1 | 1 | 10-8026 | 88861425 |

PRODUCT DESCRIPTION AND FUNCTION:

The Soft Bristle Interior Cleaner Brush can be used to safely clean all soft textiles within vehicle interiors. Soft fibers mounted in a rigid polyethylene block provide the proper level of agitation to clean a wide variety of interior surfaces.

PRODUCT FEATURES AND BENEFITS:

- Soft brush fibers were developed specifically for use on soft textiles
- Designed to work on all upholstery without damaging fabric
- Bristles are mounted to provide proper level of agitation to clean a variety of surfaces

Leather and Vinyl Conditioner



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 32 oz. | 12 | 10-8018 | 88861402 |

PRODUCT DESCRIPTION AND FUNCTION:

Leather and Vinyl Conditioner is a post-cleaning product designed to recondition and protect leather and vinyl surfaces. This vinyl and leather conditioner softens and restores luster to these materials by replenishing oils.

Product is not available for sale in the State of California. Must be compliant to C.A. S.B. 258.

PRODUCT FEATURES AND BENEFITS:

- Multi-surface product can be used on low-gloss and high-gloss leather and vinyl
- Designed for use after cleaning with Leather, Vinyl, and Plastic Cleaner to fully clean and recondition leather and vinyl surfaces
- Replenishes oils to leather and vinyl surfaces to soften and restore luster

Leather and Vinyl Conditioner



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 8 oz. | 12 | 10-8030 | 88861406 |

PRODUCT DESCRIPTION AND FUNCTION:

Leather and Vinyl Conditioner is a post-cleaning product designed to recondition and protect leather and vinyl surfaces. This vinyl and leather conditioner softens and restores luster to these materials by replenishing oils.

Product is not available for sale in the State of California. Must be compliant to C.A. S.B. 258.

PRODUCT FEATURES AND BENEFITS:

- Multi-surface product can be used on low-gloss and high-gloss leather and vinvl
- Designed for use after cleaning with Leather, Vinyl, and Plastic Cleaner to fully clean and recondition leather and vinyl surfaces
- Replenishes oils to leather and vinyl surfaces to soften and restore luster

Leather, Vinyl and Plastic Cleaner



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 32 oz. | 12 | 10-8017 | 88861401 |

PRODUCT DESCRIPTION AND FUNCTION:

Leather, Vinyl, and Plastic Cleaner is formulated to remove the toughest stains. This vinyl, plastic, and leather cleaner safely and effectively eliminates ink, tar, grease, crayons, and markers.

Product is not available for sale in the State of California. Must be compliant to C.A. S.B. 258.

PRODUCT FEATURES AND BENEFITS:

- Multi-surface product can be used on plastic and both low-gloss and high-gloss leather and vinyl
- Formulated with natural citrus degreasers to effectively remove stains without the danger of damage by harsh chemicals
- Designed for use before conditioning with Leather and Vinyl Conditioner to fully clean leather and vinyl surfaces

Leather, Vinyl and Plastic Cleaner



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 8 oz. | 12 | 10-8029 | 88861405 |

PRODUCT DESCRIPTION AND FUNCTION:

Leather, Vinyl, and Plastic Cleaner is formulated to remove the toughest stains. This vinyl, plastic, and leather cleaner safely and effectively eliminates ink, tar, grease, crayons, and markers.

Product is not available for sale in the State of California. Must be compliant to C.A. S.B. 258.

- Multi-surface product can be used on plastic and both low-gloss and high-gloss leather and vinyl
- Formulated with natural citrus degreasers to effectively remove stains without the danger of damage by harsh chemicals
- Designed for use before conditioning with Leather and Vinyl Conditioner to fully clean leather and vinyl surfaces

Microfiber Towel (Ultra Fine)



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 15" x 15" | 12 | 10-8063 | 88865237 |

PRODUCT DESCRIPTION AND FUNCTION:

Ultra Fine Microfiber Towels are a workhorse towel that can be used for a variety of purposes on vehicle interior and exterior surfaces. It is excellent for general cleaning, polishing, drying wheels, and a host of other appearance-related jobs.

PRODUCT FEATURES AND BENEFITS:

- Contains 200,000 strands in every square inch of highly refined, loop-woven microfiber to increase cleaning capabilities
- FSpecially designed to absorb seven times its weight in applicable product and picks up dust and micro-particles like a magnet
- Lint-free and non-abrasive materials cleans effectively without scratching or causing damage

Odor Eliminator



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 32 oz. | 12 | 10-8027 | 88861431 |

PRODUCT DESCRIPTION AND FUNCTION:

Odor Eliminator is specially designed to remove odors at the source inside vehicles and HVAC systems. Suggested uses include upholstery, headliners, carpets, floor mats, storage areas, and more. This product is excellent for eliminating musky odors from wet vehicle interiors. Product is not available for sale in the State of California. Must be compliant to C.A. S.B. 258.

PRODUCT FEATURES AND BENEFITS:

- No fragrance added removes unwanted smells without adding an overpowering cleaner scent
- · Water-based formula will not add additional chemicals to the air
- Product is sprayed directly into the air intake when being used in the ventilation system, eliminating odors at the source

Odor Eliminator



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 8 oz. | 12 | 10-8028 | 88861432 |

PRODUCT DESCRIPTION AND FUNCTION:

Odor Eliminator is specially designed to remove odors at the source inside vehicles and HVAC systems. Suggested uses include upholstery, headliners, carpets, floor mats, storage areas, and more. This product is excellent for eliminating musky odors from wet vehicle interiors. Product is not available for sale in the State of California. Must be compliant to C.A. S.B. 258.

PRODUCT FEATURES AND BENEFITS:

- No fragrance added removes unwanted smells without adding an overpowering cleaner scent
- Water-based formula will not add additional chemicals to the air
- Product is sprayed directly into the air intake when being used in the ventilation system, eliminating odors at the source

Optikleen® (Windshield Washer Solvent)



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 32 oz. | 12 | 01051515 | 01051515 |

PRODUCT DESCRIPTION AND FUNCTION:

Optikleen® Windshield Washer Solvent is a unique formulation designed for all-season use in vehicle window washer systems. This is a concentrated product that can be diluted to meet your particular freeze protection needs.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

PRODUCT FEATURES AND BENEFITS:

- Specially formulated with outstanding cleaning agents to remove bug matter and road film without smearing or streaking, while remaining safe for metal, glass, and paint surfaces
- Excellent cold weather performance protects against freezing down to -26 degrees Fahrenheit (-32 degrees Celsius) when properly diluted
- Contains surfactants that limit safety hazards by minimizing oily dirt smears on the windshield

Optikleen® (Windshield Washer Solvent)



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 32 oz. | 720 (Pallet) | N/A | 12378465 |

PRODUCT DESCRIPTION AND FUNCTION:

Optikleen® Windshield Washer Solvent is a unique formulation designed for all-season use in vehicle window washer systems. This is a concentrated product that can be diluted to meet your particular freeze protection needs.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

- Specially formulated with outstanding cleaning agents to remove bug matter and road film without smearing or streaking, while remaining safe for metal, glass, and paint surfaces
- Excellent cold weather performance protects against freezing down to -26 degrees Fahrenheit (-32 degrees Celsius) when properly diluted
- Contains surfactants that limit safety hazards by minimizing oily dirt smears on the windshield



Optikleen® (Windshield Washer Solvent)

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 55 gallon drum | 4 | N/A | 88865785 |

PRODUCT DESCRIPTION AND FUNCTION:

Optikleen® is a unique, concentrated formulation designed for vehicle window washer systems. Contains outstanding cleaning agents to clean the glass without smearing or streaking. Safe for metal, glass and painted surfaces. Protects against freezing down to minus 26° Fahrenheit. Use with adequate ventilation.

Ouick Detailer



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 16 oz. | 6 | 10-8047 | 88865219 |

PRODUCT DESCRIPTION AND FUNCTION:

Quick Detailer is an easy-to-use spray-and-wipe wax and quick detail gloss enhancer. This product effectively restores a just-waxed wet looking shine in minutes without leaving wax buildup on painted or exterior plastic surfaces. A single spray wipes away fingerprints, water spots, dust, and other harmful contaminants. Quick Detailer provides a protective shine between waxes and creates an invisible barrier over any treated surface.

Product is not available for sale in the State of California. Must be compliant to C.A. S.B. 258.

PRODUCT FEATURES AND BENEFITS:

- High-lubricity spray wax with specialized ingredients that provide unparalleled surface clarity, intensity, and shine
- Contains highly-reflective polymers which form a protective coat that bonds to the paint's sealant or wax finish, and leave the vehicle with a slick, shiny, just-polished surface, extending the life of any sealant or wax
- Carnauba wax formulation performs even in hot, humid climates without streaking, cloudiness, or hazy patches

Rain Repellent Treatment **Container Size**

Unit Package ACDelco Part Number GM Part Number 1 applicator 24 10-8070 88864552

PRODUCT DESCRIPTION AND FUNCTION:

Rain Repellent Treatment makes glass surfaces water resistant while significantly improving driver visibility. This product can be applied to any exterior glass surface (not just the windshield) in less than ten minutes. Originally developed for the aviation industry, it causes rain to bead up and roll off the glass, shielding its surface longer than other glass coating products.

For Professional Use Only. Not for Retail Sale.

Product is not available for sale in the State of California. Must be compliant to C.A. S.B. 258.

PRODUCT FEATURES AND BENEFITS:

- · Patented hydrophobic formula creates a chemical bond with any windshield, side window, or mirror to make glass surfaces water resistant and to improve driver visibility
- All-season performance formula repels rain, sleet, and snow, and makes it easier to remove ice, snow, bugs, and dirt, to help provide clear visibility day and night, even in inclement weather
- Easy-to-use and versatile treatment can be applied to any exterior glass surface in less than ten minutes

Stainless Steel and Chrome Cleaner and Polish



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 8 oz. | 1 | 10-8073 | 88864067 |

PRODUCT DESCRIPTION AND FUNCTION:

Stainless Steel and Chrome Cleaner and Polish is excellent for restoring the original appearance to tarnished, rusted, stained, or dulled surfaces, leaving a bright silicone shine behind. This product is a complex blend of oil, water, silicone, emulsifiers, pumice, and polishing agents. Product is not available for sale in the State of California. Must be compliant to C.A. S.B. 258.

PRODUCT FEATURES AND BENEFITS:

- High-quality formulation cleans and rejuvenates the stainless steel and chrome surfaces on your vehicle
- Specially chemically engineered to restore original shine to tarnished, stained, or dulled stainless steel or chrome surfaces
- Contains silicone and polishing agents to leave behind a bright shine

Touch Screen Cleaner



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 3.4 oz. | 12 | 10-8076 | 88865945 |

PRODUCT DESCRIPTION AND FUNCTION:

Touch Screen Cleaner is a gentle and effective cleaner that cleans touch screens in cars, trucks and other vehicles equipped with touch screens. It safely removes oil, grease, grime and other non-abrasive stains. It can be used on touch screen surfaces including GPS, vehicle DVD players, cell phones, tablets, and laptops.

Instructions: Spray Touch Screen Cleaner on a soft, clean microfiber cloth. Use this cloth to gently rub the surface to be cleaned. For stubborn, dried-on stains, the process may need to be repeated until surface is clean. For best results, the cleaner should always be used with a soft, microfiber cloth. Do not use paper towels or other types of wipes that could scratch the touch screen surface.

Product is not available for sale in the State of California. Must be compliant to C.A. S.B. 258.



Three Piece Vehicle Cleaning Kit

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|-------------------|--------------|---------------------|----------------|
| 3 - 4 oz. bottles | 12 | 10-8074 | 88864155 |

PRODUCT DESCRIPTION AND FUNCTION:

This three piece Vehicle Care cleaning kit includes:

88865228 - Car Wash Shampoo - 4 oz.

88865229 - Cleaner Wax - 4 oz.

88865231 - Vinyl, Rubber and Tire Dressing - 4 oz.

Product is not available for sale in the State of California. Must be

compliant to C.A. S.B. 258.

Upholstery/Carpet Stain Remover - Gold Formula



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 32 oz. | 12 | 10-8033 | 88861403 |

PRODUCT DESCRIPTION AND FUNCTION:

Upholstery/Carpet Stain Remover – Gold Formula is a professional strength cleaner. This upholstery/carpet stain remover is formulated to remove the toughest food and protein-based stains from interior fabrics and carpeting.

Product is not available for sale in the State of California. Must be compliant to C.A. S.B. 258.

PRODUCT FEATURES AND BENEFITS:

- Specifically designed to treat food and protein-based stains
- Eliminates stains from foods and beverages, such as butter/margarine, chocolate, mustard, ketchup, vegetable oil, salad dressing, mayonnaise, jelly, coffee, tea, cola, wine
- Also removes stains from grass, mildew, latex paint, vomit, blood, and urine

Upholstery/Carpet Stain Remover - Gold Formula



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|-----------------------|
| 8 oz. | 12 | 10-8031 | 88861407 |

PRODUCT DESCRIPTION AND FUNCTION:

Upholstery/Carpet Stain Remover – Gold Formula is a professional strength cleaner. This upholstery/carpet stain remover is formulated to remove the toughest food and protein-based stains from interior fabrics and carpeting.

Product is not available for sale in the State of California. Must be compliant to C.A. S.B. 258.

PRODUCT FEATURES AND BENEFITS:

- Specifically designed to treat food and protein-based stains
- Eliminates stains from foods and beverages, such as butter/margarine, chocolate, mustard, ketchup, vegetable oil, salad dressing, mayonnaise, jelly, coffee, tea, cola, wine
- Also removes stains from grass, mildew, latex paint, vomit, blood, and urine

Upholstery/Carpet Stain Remover - Red Formula



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|-----------------------|
| 32 oz. | 12 | 10-8020 | 88861404 |

PRODUCT DESCRIPTION AND FUNCTION:

Upholstery/Carpet Stain Remover – Red Formula is a professional strength cleaner. This upholstery/carpet stain remover is formulated to remove the toughest ink, grease, and oil stains from interior fabrics and carpeting.

Product is not available for sale in the State of California. Must be compliant to C.A. S.B. 258.

PRODUCT FEATURES AND BENEFITS:

- Specifically designed to treat ink, grease, and oil-based stains
- Eliminates stains from everyday objects, such as cosmetics (lipstick, nail polish), crayons, ink, gum, and markers
- Also removes stains from grease (motor), ink, iodine, rust, tar, shoe polish, and oil

Upholstery/Carpet Stain Remover - Red Formula



| Container Size | Unit Package | ACDelco Part Number | GM Part Number | |
|----------------|--------------|---------------------|-----------------------|--|
| 8 oz. | 12 | 10-8032 | 88861408 | |

PRODUCT DESCRIPTION AND FUNCTION:

Upholstery/Carpet Stain Remover – Red Formula is a professional strength cleaner. This upholstery/carpet stain remover is formulated to remove the toughest ink, grease, and oil stains from interior fabrics and carpeting.

Product is not available for sale in the State of California. Must be compliant to C.A. S.B. 258.

- Specifically designed to treat ink, grease, and oil-based stains
- Eliminates stains from everyday objects, such as cosmetics (lipstick, nail polish), crayons, ink, gum, and markers
- Also removes stains from grease (motor), ink, iodine, rust, tar, shoe polish, and oil



Vinyl, Rubber and Tire Dressing

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 16 oz. | 6 | 10-8050 | 88865221 |

PRODUCT DESCRIPTION AND FUNCTION:

Vinyl, Rubber, and Tire Dressing is a premium, non-greasy, dry-to-touch interior and exterior cleaner, conditioner, and protectant. This product provides long-lasting gloss, shine, and protection to vinyl, rubber, and tire surfaces. Prevent premature aging and fading with a simple one step application of Vinyl, Rubber and Tire Dressing. This product is not suitable for interior surfaces with a matte finish. Product is not available for sale in the State of California. Must be compliant to C.A. S.B. 258.

PRODUCT FEATURES AND BENEFITS:

- Engineered with a pH balanced conditioning formula that penetrates beyond the surface to help rejuvenate and maintain the pliability and integrity of the covering
- Specially formulated with UV blocking agents that help keep surfaces from cracking, fading, and hardening, defending them against the harmful rays of the sun
- Multi-surface product that is effective on rubber, vinyl, trim, vinyl tops, and dashboards, and can also be used on other vinyl surfaces like briefcases, purses, shoes, and furniture. Not suitable for interior surfaces with a matte finish



Vinyl, Rubber and Tire Dressing

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 4 oz. | 30 | 10-8051 | 88865231 |

PRODUCT DESCRIPTION AND FUNCTION:

Vinyl, Rubber, and Tire Dressing is a premium, non-greasy, dry-to-touch interior and exterior cleaner, conditioner, and protectant. This product provides long-lasting gloss, shine, and protection to vinyl, rubber, and tire surfaces. Prevent premature aging and fading with a simple one step application of Vinyl, Rubber and Tire Dressing. This product is not suitable for interior surfaces with a matte finish. Product is not available for sale in the State of California. Must be compliant to C.A. S.B. 258.

PRODUCT FEATURES AND BENEFITS:

- Engineered with a pH balanced conditioning formula that penetrates beyond the surface to help rejuvenate and maintain the pliability and integrity of the covering
- Specially formulated with UV blocking agents that help keep surfaces from cracking, fading, and hardening, defending them against the harmful rays of the sun
- Multi-surface product that is effective on rubber, vinyl, trim, vinyl tops, and dashboards, and can also be used on other vinyl surfaces like briefcases, purses, shoes, and furniture. Not suitable for interior surfaces with a matte finish

Wheel and Rim Cleaner



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 16 oz. | 6 | 10-8048 | 88865220 |

PRODUCT DESCRIPTION AND FUNCTION:

Wheel and Rim Cleaner is ideal for cleaning and degreasing all varieties of wheels and rims. This product safely removes brake dust, oxidation, oil, dirt, and rust. It dissolves grease without the risk of damaging the wheel.

Product is not available for sale in the State of California. Must be compliant to C.A. S.B. 258.

PRODUCT FEATURES AND BENEFITS:

- Unique gel formula clings to the wheels, for increased time in contact with the wheel, allowing continuous break down of road grime, brake dust, and grease
- Quality cleaner safely dissolves grease without causing wheel damage or corrosion
- Highly concentrated solution that can be diluted for various cleaning needs

White Sidewall Cleaner



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 1 gal. | 6 | 10-8034 | 01050175 |

PRODUCT DESCRIPTION AND FUNCTION:

White Sidewall Cleaner is specifically formulated to restore brightness to tire whitewalls and raised white lettering. It is safe for use on rubber surfaces and does not require pre-cleaning. This product is a water-based alkaline that effectively removes grease, grime, and dirt. White Sidewall cleaner is great at prepping tires for today's high-tech tire dressings.

For Professional Use Only. Not for Retail Sale.

Product is not available for sale in the State of California. Must be compliant to C.A. S.B. 258.

- Designed specifically for cleaning whitewall and raised white lettering on black sidewall tires, effectively removing all types of soils and whitening dingy tire surfaces
- Water-based alkaline cleaner removes grease, grime, and dirt without damaging the rubber surface
- Easy-to-use formula does not require pre-cleaning



Auto Trak II Transfer Case Fluid

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 33.8 oz. | 12 | 10-4017 | 88900402 |

PRODUCT DESCRIPTION AND FUNCTION:

Auto Trak II Transfer Case Fluid is approved for use in GM automatic four-wheel drive vehicles with transfer cases as recommended in the owner's manual or GM service bulletins. This transfer case fluid has improved oxidation resistance for extended life and withstands extended high-temperature operation.

PRODUCT FEATURES AND BENEFITS:

- Specifically approved for use in GM automatic four-wheel drive vehicles with transfer cases
- · Improved oxidation resistance for extended life
- Withstands extended high-temperature operation

Axle Lubricant GL-5 (80W-90)



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 23 oz. | 12 | 10-4051 | 89021669 |

PRODUCT DESCRIPTION AND FUNCTION:

Axle Lubricant GL-5 (80W-90) is a special formula multi-purpose axle lubricant for use with conventional type axles. The formula contains superior oxidation resistance and longer seal life. Axle Lubricant GL-5 (80W-90) does not contain a limited slip additive. This product satisfies General Motors Specification No. 9985182 for rear axle factory fill. It is for use in passenger cars only, and is not intended for use in trucks.

PRODUCT FEATURES AND BENEFITS:

- Meets American Petroleum Institute (API) GL-5 specifications for use in severe conditions
- Meets General Motors Specification No. 9985182 meaning that the fluid meets a wide range of external and internal specifications including SAE J306
- Meets ASTM STP-512A meaning that the lubricant resists deposit formation and assists in protecting against rippling, ridging, pitting, or spalling

DEXRON® Gear Oil (75W-90)



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 32 fl. oz. | 12 | 10-4108 | 19352759 |

PRODUCT DESCRIPTION AND FUNCTION:

DEXRON® Gear Oil (75W-90), meeting GL-5, is a fully synthetic gear oil designed for long-drain service. It is specifically formulated to provide long service life and extended gear life in automotive differentials operating under varying conditions of speed, load, temperature and torque. This fluid combines excellent oxidation resistance and thermal stability at high temperatures with outstanding low-temperature properties to ensure excellent performance over a wide temperature range. ACDelco DEXRON® Gear Oil (75W-90) has excellent water-separating properties to help prevent the formation of emulsions and retain its lubricating properties even in the presence of a small amount of water.

DEXRON® LS Gear Oil GL-5 (75W-90)



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 32 oz. | 12 | 10-4034 | 88862624 |

PRODUCT DESCRIPTION AND FUNCTION:

DEXRON® LS Gear Oil GL-5 (75W-90) is for the lubrication and service of 2007+ manual transmissions and transfer cases. This gear oil already contains a limited slip friction modifier. A top treat additive is not needed.

PRODUCT FEATURES AND BENEFITS:

- Specifically designed for the lubrication and service of model year 2007 and newer manual transmissions and transfer cases
- Product already contains a limited slip friction modifier
- No need to use a top treat additive

Limited Slip Axle Lubricant Additive



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 4 oz. | 1 | 89021958 | 89021958 |

PRODUCT DESCRIPTION AND FUNCTION:

Refer to service information for use.

PRODUCT FEATURES AND BENEFITS:

• Required for passenger car applications with limited slip axles.



Limited Slip Axle Lubricant Additive

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 4 oz. | 12 | 10-4003 | 88900330 |

PRODUCT DESCRIPTION AND FUNCTION:

Limited Slip Axle Lubricant Additive reduces friction and noise in the rear axle.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

PRODUCT FEATURES AND BENEFITS:

· Required for passenger car applications with limited slip axles.



Rear Axle Lubricant GL-5 (75W-85)

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 33.8 oz. | 4 | 10-4032 | 92184900 |

PRODUCT DESCRIPTION AND FUNCTION:

Rear Axle Lubricant GL-5 (75W-85) is a full synthetic SAE 75W-85 final drive lubricant recommended for ZF limited slip differentials with carbon linings such as the 2008-2009 Pontiac G8.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

PRODUCT FEATURES AND BENEFITS:

- Specially recommended for ZF limited slip differentials with carbon linings
- High quality full synthetic SAE 75W-85 final drive lubricant
- High viscosity lubricant to better protect axle's moving components



Rear Axle Lubricant - High Efficiency GL-5 (75W-85)

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 32 oz. | 12 | 10-4091 | 19300457 |

PRODUCT DESCRIPTION AND FUNCTION:

Rear Axle Lubricant - High Efficiency GL-5 (75W-85) is an enhanced, specially formulated synthetic hypoid gear lubricant made from Group III base stocks for improved performance intended to be used with AAM axle products. Refer to service manual for GM vehicle application.

For Professional Use Only. Not for Retail Sale.

Synthetic Axle Lubricant GL-5 (75W-90)



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 32 oz. | 12 | 10-4016 | 88900401 |

PRODUCT DESCRIPTION AND FUNCTION:

Synthetic Axle Lubricant GL-5 (75W-90) is a heavy duty extreme temperature pressure GL-5 axle lubricant. It withstands the high temperatures encountered during extended high-speed operation and heavy towing while also retaining excellent fluidity at cold temperatures. The fully synthetic formulation of Synthetic Axle Lubricant GL-5 (75W-90) contains superior oxidation and thermal stability.

PRODUCT FEATURES AND BENEFITS:

- Meets American Petroleum Institute (API) GL-5 specification for use in severe condition
- Superior formula manufactured to withstand high temperatures encountered during extended high-speed operation while retaining fluidity at cold temperatures





| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 1 gal. | 4 | 10-4099 | 88861719 |

PRODUCT DESCRIPTION AND FUNCTION:

Synthetic Axle Lubricant GL-5 (75W-90) is a heavy duty extreme temperature pressure GL-5 axle lubricant. It withstands the high temperatures encountered during extended high-speed operation and heavy towing while also retaining excellent fluidity at cold temperatures. The fully synthetic formulation of Synthetic Axle Lubricant GL-5 (75W-90) contains superior oxidation and thermal stability.

- Meets American Petroleum Institute (API) GL-5 specification for use in severe condition
- Superior formula manufactured to withstand high temperatures encountered during extended high-speed operation while retaining fluidity at cold temperatures



Synthetic Axle Gear Lubricant GL-5 (75W-140)

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 32 oz. | 12 | 10-4054 | 89021524 |

PRODUCT DESCRIPTION AND FUNCTION:

Synthetic Axle Gear Lubricant (75W-140) is a fully synthetic, wide viscosity span automotive GL-5 gear lubricant. It has superior low/ high temperature performance to help ensure that bearings, gears, and seals receive proper lubrication at temperatures as low as -40 degrees Fahrenheit (-40 degrees Celsius). Synthetic Axle Lubricant (75W-140) also provides load-carrying ability and protection from gear wear at elevated temperatures encountered in high ambient or trailer tow and other severe service applications.

PRODUCT FEATURES AND BENEFITS:

- Superior thermal and oxidation stability for increased fluid life and performance
- Excellent low temperature fluidity for superior cold start lubrication
- Compatible with most conventional automotive gear oils for a wide range of use and applications

Synthetic Gear Oil GL-5 (75W-140)



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 33.8 oz. | 12 | 10-4053 | 89021809 |

PRODUCT DESCRIPTION AND FUNCTION:

Synthetic Gear Oil GL-5 (75W-140) is an American Petroleum Institute (API) GL-5 oil for use on the 2004-2006 Pontiac GTO.

PRODUCT FEATURES AND BENEFITS:

 Meets American Petroleum Institute (API) GL-5 specification for use in severe conditions

Synthetic Transfer Case Fluid



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|----------------------------|-----------------------|
| 32 oz. | 6 | 10-4100 | 19331044 |

PRODUCT DESCRIPTION AND FUNCTION:

Synthetic Transfer Case Fluid is a high performance transfer case fluid for active transfer case applications with clutch systems. Based on synthetic base fluids, this product is an optimum performance transfer case fluid under most severe operating conditions. ACDelco Synthetic Transfer Case Fluid has excellent oxidative stability, superior low temperature fluidity, excellent thermal properties, very good shear and friction stability, and excellent antifoaming properties.

Transfer Case Fluid



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 33.8 oz. | 12 | 10-4044 | 88861950 |

PRODUCT DESCRIPTION AND FUNCTION:

Transfer Case Fluid is designed to optimize vehicle performance while operating in a wide range of environments and especially in low ambient temperature applications. This transfer case fluid combines select base oils and an advanced additive package to deliver a variety of lubricant performance properties required by various applications. This product should not be used in passenger vehicles with automatic transmissions.

WARNING: Reproductive Harm - www.P65Warnings.ca.gov.

PRODUCT FEATURES AND BENEFITS:

- Enhanced frictional properties to optimize clutch and power take-off (PTO) performance control as well as improving clutch life and noise reduction
- Compatible with latest clutch materials and elastomers for longer clutch life, reduced leakage, and reliable response
- High viscosity index with improved shear stability for enhanced viscosity retention and longer equipment life

VERSATRAK® Fluid GL-5 (75W-85)



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 16.9 oz. | 12 | 10-4058 | 12378514 |

PRODUCT DESCRIPTION AND FUNCTION:

VERSATRAK® Fluid 75W-85, GL-5 is a blend of synthetic base oils and performance additives specially formulated to give the proper friction characteristics, gear protection, and oxidation resistance needed for the transfer case and carrier assembly differential in the VERSATRAK All-Wheel Drive System. Do not use VERSATRAK Fluid in standard or limited slip rear axles. Use VERSATRAK fluid only in applications that specify VERSATRAK fluid.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

- Blended synthetic base oils and performance additives drives power from the engine to the front and rear axles
- Specifically designed for use only in applications that require VERSATRAK fluid
- Specially formulated to give proper friction characteristics, gear protection, and oxidation resistance needed for the transfer case and carrier assembly differential



Anti-Corrosion Compound (Wax-Based) - Aerosol

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 12.3 oz. | 12 | 10-6006 | 12378399 |

PRODUCT DESCRIPTION AND FUNCTION:

This product is an amber colored, wax-based anti-corrosion compound. It can be used in all vehicle cavity areas to treat bare metal or to replace the original materials. Can apply to all interior cavity and box areas, interior of wheel openings, front and rear fenders, all interior door areas, inside base or center pillars, lower hatch back, and rear compartment areas.

PRODUCT FEATURES AND BENEFITS:

 Product should not be sprayed on electrical components, wood trim or fabric



Rubberized Undercoating - Aerosol

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 14.3 oz. | 12 | 10-1017 | 12378398 |

PRODUCT DESCRIPTION AND FUNCTION:

Rubberized Undercoating is ideal for protecting automotive undercarriages and door skins. It may be painted over with flexible automotive enamels or lacquers. This product sprays easily, remains flexible after drying, and resists corrosion.

WARNING: Reproductive Harm - www.P65Warnings.ca.gov.

PRODUCT FEATURES AND BENEFITS:

- This product includes a spray nozzle with extension tube for small or difficult to reach areas
- Specially designed to protect automotive undercarriages and door ckins.
- Engineered to remain flexible after drying and resist corrosion



Rust and Corrosion Inhibitor - Aerosol

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|----------------------------|-----------------------|
| 14 oz. | 2 | 10-6005 | 19257664 |

PRODUCT DESCRIPTION AND FUNCTION:

Works as a paint primer over rust. It is designed to help prevent and repair rust and corrosion on the exterior of metal structures, metal parts, and metal structural components. This flexible coating will not yellow, chalk, crack or peel. Meets ASTMA A-780 specifications.

Rust Penetrant and Inhibitor - Aerosol



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 11 oz. | 12 | 10-4020 | 88862628 |

PRODUCT DESCRIPTION AND FUNCTION:

Rust Inhibitor and Penetrant helps loosen metal fasteners, nuts and bolts, and components in any other place where metal-to-metal contact occurs. It is formulated to dissolve lead oxide deposit formations on manifold valve shafts. This rust inhibitor product also works as a lubricant, allowing heat control valves to operate freely. For Professional Use Only. Not for Retail Sale. WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

PRODUCT FEATURES AND BENEFITS:

- This product contains a special blend of solvents and lubricants to tackle the toughest rust, corrosion, and other time-formed oxides
- Aids in the loosening of components in places where metal-to-metal contact occurs
- Multipurpose product acts as a lubricant to allow heat control valves to operate freely

Sound Deadening Pad Package



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|-----------------------|--------------|---------------------|-----------------------|
| 7.5" x 19.5" (4 pads) | 1 | 10-7013 | 12378195 |

PRODUCT DESCRIPTION AND FUNCTION:

These pads are designed to absorb vibration in sheet metal panels in conjunction with a sound absorbent material to provide effective sound insulation. Package contains 4 pads, each approximately 7.5" x 19.5". Pads are self-adhesive, flexible, easy-to-cut and paintable.



DOT 3 GMW Brake and Clutch Fluid

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 16 fl. oz. | 24 | 10-4110 | 19353126 |

PRODUCT DESCRIPTION AND FUNCTION:

GMW DOT 3 Brake and Clutch Fluid is recommended for all vehicles requiring DOT 3 brake fluid. This product is compatible with all disc and drum brake systems. It contains enhanced corrosion inhibitors to resist corrosion and excess wear.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

Brake and Clutch Fluid, DOT 4 GMW



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 16 oz. | 1 | 10-4086 | 19299570 |

PRODUCT DESCRIPTION AND FUNCTION:

Clutch and Brake Fluid, DOT 4 GMW is a premium brake and hydraulic clutch fluid for systems requiring a FMVSS No. 116 DOT 4, ISO 4925 Class 6. Clutch and Brake Fluid, DOT 4 GMW is suitable for all applications requiring a DOT 4 performance level brake fluid and meets GMW 3356. The Clutch and Brake Fluid, DOT 4 GMW protects internal components from corrosion under normal use and service. WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

PRODUCT FEATURES AND BENEFITS:

- Premium brake and hydraulic clutch fluid that protects internal components from corrosion under normal use
- High boiling point to minimize brake fluid boiling and vapor lock
- Excellent low temperature capability and stability when used where lower cold viscosities are required

Brake Parts Cleaner (10% VOC) - Aerosol



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 15 oz. | 12 | 10-6014 | 19287401 |

PRODUCT DESCRIPTION AND FUNCTION:

Brake Parts Cleaner (10% VOC) is a specially formulated low VOC brake cleaner that removes oil, grease, brake fluids, dirt, and contaminants from brake components such as brake shoes, drums, springs, brake plates, calipers, pads, and rotors. Brake Parts Cleaner (10% VOC) quickly and effectively frees brake parts to enable the brakes to function properly without mechanical binding. Brake Parts Cleaner (10% VOC) meets the California Air Resource Board (CARB) strict air quality control regulations. This product can be sold in all 50 states. WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

PRODUCT FEATURES AND BENEFITS:

- Easy-to-use aerosol spray can leaves no residue, is quick drying, and low odor
- Has a wide range of use applications and can also be used to clean electrical components
- Safe for all brake systems and can be used with disc, drum, and ABS systems

Brake Parts Cleaner (10% VOC)



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 53 gallons | 1 | 10-6026 | 19331927 |

PRODUCT DESCRIPTION AND FUNCTION:

Brake Parts Cleaner is a non-chlorinated brake cleaner that has been specially formulated to remove oil, grease, brake fluid, dirt and contaminates from brake components such as brake shoes, drums, springs, brake plates, calipers, pads and rotors. It is also an effective cleaner for clutch, transmission and engine parts. This product does not contain chlorinated solvents. Do not apply to brake linings, plastic or rubber parts (including seals). Protect such parts from overspray during cleaning.

INSTRUCTIONS:

- Loose brake dust may contain asbestos. Remove all loose dust with an enclosed cylinder/HEPA vacuum. To avoid creating airborne dust that may contain asbestos, do not use brake parts cleaner to spray away dry, loose dirt.
- Spray brake parts cleaner on all areas except linings, painted surfaces, plastic and/or rubber parts. Keep nozzle at least 12 inches from the surface of the part to avoid creating airborne dust which may contain asbestos.
- Clean and dry all areas of wheel bearing contact and caliper slide surfaces before applying lubricant. If a cloth is used to dry the surfaces, please dispose of it properly as it may contain asbestos dust
- Apply appropriate lubricant to all components that require lubrication, such as backing plates, adjusting screw assembly, caliper slides and wheel bearings.
- Do not apply brake parts cleaner to components after lubricant application.

This product meets the California Air Resource Board (CARB) strict air quality control regulations.

For Professional Use Only. Not for Retail Sale.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.



Brake Parts Cleaner (45% VOC) - Aerosol

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 15 oz. | 12 | 10-6013 | 19287400 |

PRODUCT DESCRIPTION AND FUNCTION:

Brake Parts Cleaner (45% VOC) is a non-chlorinated brake cleaner that has been specially formulated to remove oil, grease, brake fluid, dirt, and contamination from brake components such as brake shoes, drums, springs, brake plates, calipers, pads, and rotors.

This product is not for sale in California, Utah, Delaware and New Hampshire due to state regulations.

PRODUCT FEATURES AND BENEFITS:

- The easy to use formula cleans and degreases brake components with disassembly
- Improves brake performance by reducing brake dust and helping to reduce brake squealing and chattering
- Safe for all brake systems and can be used with disc, drum, and ABS systems

Brake Parts Cleaner (45% VOC)



Container SizeUnit PackageACDelco Part NumberGM Part Number53 gallons110-602788865626

PRODUCT DESCRIPTION AND FUNCTION:

Brake Parts Cleaner is a non-chlorinated brake cleaner that has been specially formulated to remove oil, grease, brake fluid, dirt and contaminates from brake components such as brake shoes, drums, springs, brake plates, calipers, pads and rotors. It is also an effective cleaner for clutch, transmission and engine parts. This product does not contain chlorinated solvents. Do not apply to brake linings, plastic or rubber parts (including seals). Protect such parts from overspray during cleaning.

INSTRUCTIONS:

- Loose brake dust may contain asbestos. Remove all loose dust with an enclosed cylinder/HEPA vacuum. To reduce the risk of airborne asbestos fibers, do not use brake parts cleaner to spray away dry, loose dirt.
- Spray brake parts cleaner on all areas except linings, painted surfaces, plastic and/or rubber parts. Keep nozzle at least 12 inches from the surface of the part to avoid creating airborne dust which may contain asbestos.
- Clean and dry all areas of wheel bearing contact and caliper slide surfaces before applying lubricant. If a cloth is used to dry the surfaces, please dispose of it properly as it may contain asbestos dust.
- Apply appropriate lubricant to all components that require lubrication, such as backing plates, adjusting screw assembly, caliper slides and wheel bearings.
- Do not apply brake parts cleaner to components after lubricant application.

This product is not for sale in California, Utah, Delaware and New Hampshire due to state VOC regulations.

For Professional Use Only. Not for Retail Sale.



Carburetor and Choke Cleaner (10% VOC) - Aerosol

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 15 oz. | 12 | 10-6016 | 19287403 |

PRODUCT DESCRIPTION AND FUNCTION:

Choke and Carburetor Cleaner (10% VOC) is a hexane-free, heavy-duty, non-chlorinated aerosol designed to address deposit formation on carburetors and throttle body injection (TBI) units. It deals effectively with dirt and fuel-related gum, varnish, and carbon deposits.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

PRODUCT FEATURES AND BENEFITS:

- Hexane-free, heavy-duty, non-chlorinated formula removes deposit formations on carburetors and throttle body injection units
- Formulated to deal effectively with dirt and fuel related gum, varnish, and carbon deposits
- Product meets Volatile Organic Compound (VOC) standards and can be sold in all 50 states

Carburetor Tune-Up Conditioner - Aerosol



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 13 oz. | 6 | X66-A | 12302498 |

PRODUCT DESCRIPTION AND FUNCTION:

Carburetor Tune-Up Conditioner contains solvents and penetrating agents designed to remove gum, carbon, and other deposits from the fuel induction system. It frees sticky valves and sluggish compression rings. This product also removes excessive deposits from the combustion chamber. For best results, this product should be used in conjunction with an engine tune-up. For Professional Use Only. Not for Retail Sale.

WARNING: Cancer - www.P65Warnings.ca.gov.

- Specially formulated solvents and penetrating agents removed gum, carbon, and other deposits form the fuel induction system
- Assists with performance upkeep by freeing sticky valves and sluggish compression rings
- Also assists with combustion chamber upkeep by removing excess deposits



Diesel Exhaust Fluid

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 1 gal. | 4 | 10-4022 | 19286291 |

PRODUCT DESCRIPTION AND FUNCTION:

Specifically designed for diesel engines, Diesel Exhaust Fluid (DEF) is an aldehyde free, NOx (Nitrogen Oxide) reducing treatment. Diesel Exhaust Fluid is the stable, colorless, non-flammable, non-toxic primary component used to help convert NOx, an environmental pollutant, into harmless nitrogen and water. Diesel Exhaust Fluid is a mixture of 32.5% high purity synthetic urea and 67.5% deionized water. Classified as minimum risk for transportation, Diesel Exhaust Fluid meets the stringent ISO 22241 standard for purity and concentration, meets API regulations, and meets or exceeds GM OE specifications.

PRODUCT FEATURES AND BENEFITS:

- Meets GM OE specifications to be approved for use in GM vehicles as well as in non-GM diesel vehicles that have an SCR system to meet regulated NOx emissions
- High quality formula is made from high purity urea and deionized water. It contains no chemical additives or other components that could cause SCR (Selective Catalytic Reduction) system failure
- Includes a vented nozzle with 1 gallon and 2.5 gallon packages that makes pouring easy by helping to prevent glugging





| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 2.5 gal. | 2 | 10-4023 | 19286292 |

PRODUCT DESCRIPTION AND FUNCTION:

Specifically designed for diesel engines, Diesel Exhaust Fluid (DEF) is an aldehyde free, NOx (Nitrogen Oxide) reducing treatment. Diesel Exhaust Fluid is the stable, colorless, non-flammable, non-toxic primary component used to help convert NOx, an environmental pollutant, into harmless nitrogen and water. Diesel Exhaust Fluid is a mixture of 32.5% high purity synthetic urea and 67.5% deionized water. Classified as minimum risk for transportation, Diesel Exhaust Fluid meets the stringent ISO 22241 standard for purity and concentration, meets API regulations, and meets or exceeds GM OE specifications.

PRODUCT FEATURES AND BENEFITS:

- Meets GM OE specifications to be approved for use in GM vehicles as well as in non-GM diesel vehicles that have an SCR system to meet regulated NOx emissions
- High quality formula is made from high purity urea and deionized water. It contains no chemical additives or other components that could cause SCR (Selective Catalytic Reduction) system failure
- Includes a vented nozzle with 1 gallon and 2.5 gallon packages that makes pouring easy by helping to prevent glugging

Diesel Exhaust Fluid



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 55 gal. drum | 1 | 10-4026 | 88863494 |

PRODUCT DESCRIPTION AND FUNCTION:

Specifically designed for diesel engines, Diesel Exhaust Fluid (DEF) is an aldehyde free, NOx (Nitrogen Oxide) reducing treatment. Diesel Exhaust Fluid is the stable, colorless, non-flammable, non-toxic primary component used to help convert NOx, an environmental pollutant, into harmless nitrogen and water. Diesel Exhaust Fluid is a mixture of 32.5% high purity synthetic urea and 67.5% deionized water. Classified as minimum risk for transportation, Diesel Exhaust Fluid meets the stringent ISO 22241 standard for purity and concentration, meets API regulations, and meets or exceeds GM OE specifications.

For Professional Use Only. Not for Retail Sale.

PRODUCT FEATURES AND BENEFITS:

- Meets GM OE specifications to be approved for use in GM vehicles as well as in non-GM diesel vehicles that have an SCR system to meet regulated NOx emissions
- High quality formula is made from high purity urea and deionized water. It contains no chemical additives or other components that could cause SCR (Selective Catalytic Reduction) system failure
- Includes a vented nozzle with 1 gallon and 2.5 gallon packages that makes pouring easy by helping to prevent glugging

Diesel Exhaust Fluid



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 330 gal. tote | 1 | 10-4027 | 88863495 |

PRODUCT DESCRIPTION AND FUNCTION:

Specifically designed for diesel engines, Diesel Exhaust Fluid (DEF) is an aldehyde free, NOx (Nitrogen Oxide) reducing treatment. Diesel Exhaust Fluid is the stable, colorless, non-flammable, non-toxic primary component used to help convert NOx, an environmental pollutant, into harmless nitrogen and water. Diesel Exhaust Fluid is a mixture of 32.5% high purity synthetic urea and 67.5% deionized water. Classified as minimum risk for transportation, Diesel Exhaust Fluid meets the stringent ISO 22241 standard for purity and concentration, meets API regulations, and meets or exceeds GM OE specifications.

For Professional Use Only. Not for Retail Sale.

- Meets GM OE specifications to be approved for use in GM vehicles as well as in non-GM diesel vehicles that have an SCR system to meet regulated NOx emissions
- High quality formula is made from high purity urea and deionized water. It contains no chemical additives or other components that could cause SCR (Selective Catalytic Reduction) system failure
- Includes a vented nozzle with 1 gallon and 2.5 gallon packages that makes pouring easy by helping to prevent glugging





| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 1 gal. | 1 | 10-4024 | 19286318 |

PRODUCT DESCRIPTION AND FUNCTION:

To assist with ease of use when adding Diesel Exhaust Fluid to your vehicle, ACDelco offers the Diesel Exhaust Fluid Nozzle. This nozzle is specially designed and available in two sizes to fit Diesel Exhaust Fluid 1 and 2.5 gallon containers. It makes it easier to cleanly and correctly fill the DEF tank to avoid spillage. Due to the extreme chemical sensitivity of DEF, DO NOT use nozzle with other products.

PRODUCT FEATURES AND BENEFITS:

- The vented design of the nozzle makes pouring easy by helping to prevent glugging
- It is the same nozzle as originally packaged with Diesel Exhaust Fluid
- Designed to be an exact fit to Diesel Exhaust Fluid containers, and is available for either the 1 gallon or 2.5 gallon sized containers

Diesel Exhaust Fluid - Nozzle



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 2.5 gal. | 1 | 10-4025 | 19286319 |

PRODUCT DESCRIPTION AND FUNCTION:

To assist with ease of use when adding Diesel Exhaust Fluid to your vehicle, ACDelco offers the Diesel Exhaust Fluid Nozzle. This nozzle is specially designed and available in two sizes to fit Diesel Exhaust Fluid 1 and 2.5 gallon containers. It makes it easier to cleanly and correctly fill the DEF tank to avoid spillage. Due to the extreme chemical sensitivity of DEF, DO NOT use nozzle with other products.

- The vented design of the nozzle makes pouring easy by helping to prevent glugging
- It is the same nozzle as originally packaged with Diesel Exhaust

 Fluid
- Designed to be an exact fit to Diesel Exhaust Fluid containers, and is available for either the 1 gallon or 2.5 gallon sized containers



Diesel Fuel Conditioner

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 16 oz. | 6 | 10-3011 | 88861698 |

PRODUCT DESCRIPTION AND FUNCTION:

Diesel Fuel Conditioner is a multifunctional, middle distillate fuel additive package that provides cetane number increase, enhanced lubricity, corrosion protection, superior cold flow performance, and injector detergency. It is specifically formulated for low sulfur and ultra-low sulfur applications including biodiesel blends up to B20 (20% biodiesel blends). It is a non-acid, corrosion inhibition, alcohol free product.

For Professional Use Only. Not for Retail Sale. WARNING: Cancer - www.P65Warnings.ca.gov.

Fuel System Treatment Plus – Gasoline

| ACOcico tri Jens James | |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| Part Eprins Transman On Committee State of the Commi | |

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 12 oz. | 12 | 10-3012 | 88865595 |

PRODUCT DESCRIPTION AND FUNCTION:

Fuel System Treatment Plus-Gasoline is formulated to help clean the fuel system in one application, reducing combustion chamber, intake valve, and fuel injector deposits. Fuel System Treatment Plus-Gasoline helps restore performance to high mileage vehicles. It helps restore fuel economy, power, acceleration, and drivability by reducing surging, stumbling, hesitation, stalling and rough idling. It helps maintain optimum emissions systems performance. This product is not recommended for use in gasoline that contains over 50% ethanol. Treat rate is 12 oz. per 15 gallons of gasoline. WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

Fuel System Treatment Plus – Flex Fuel



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|----------------------------|----------------|
| 12 oz. | 12 | 10-3013 | 88865596 |

PRODUCT DESCRIPTION AND FUNCTION:

Fuel System Treatment Plus- Flex Fuel is a concentrated polyether amine based aftermarket gasoline additive used to provide complete fuel system cleaning of related engine deposits. Fuel System Treatment Plus- Flex Fuel is designed to provide control of carburetor, fuel injector, intake valve, and combustion chamber deposits. Fuel System Treatment Plus- Flex Fuel helps restore power and acceleration. It helps improve drivability, provide smoother acceleration and idle, and reduce tendency to stall.

A 12 oz. bottle treats up to 15 to 20 gallons of flex fuel. Pour entire bottle into a nearly empty tank and refuel with at least 15 gallons of gasoline. Fuel System Treatment Plus - Flex Fuel is for Flex Fuel vehicles only.

WARNING: Cancer - www.P65Warnings.ca.gov.

Fuel System Treatment Plus - Diesel



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 12 oz. | 12 | 10-3014 | 88865597 |

PRODUCT DESCRIPTION AND FUNCTION:

Fuel System Treatment Plus-Diesel is formulated to clean diesel fuel systems in one application, reducing deposits and restoring engine power. Fuel System Treatment Plus-Diesel is a one-tank fuel injection system cleaner formulated to provide rapid cleaning of fuel injector deposits. It is effective on nozzle deposits and internal injector deposits. Fuel System Treatment Plus-Diesel helps restore power lost due to fouled injectors and helps restore engine performance. For one tank clean-up of diesel fuel injection systems, use one bottle (12 oz.) of Fuel System Treatment Plus-Diesel per 15 gallons of fuel. Fuel System Treatment Plus-Diesel complies with Federal low sulfur content requirements for use in diesel motor vehicles and non-road engines.

WARNING: Cancer - www.P65Warnings.ca.gov.



Top Engine Cleaner – Aerosol

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 13 oz. | 12 | N/A | 01052626 |

PRODUCT DESCRIPTION AND FUNCTION:

Top Engine Cleaner cleans carburetors and fuel injection air intake cleaners, intake manifolds, intake and exhaust valves, pistons, heads and combustion chambers. It removes gum, varnish, and carbon to make tough tune ups easy and long lasting. This first step in tune up cleaners will eliminate deposits that may cause rough idle, stalling, hesitation, pings and run on. For use with 6 and 8 cylinder carbureted engines.

Do not use this product in:

- Front or rear carburetors of 3 and 2 setup, as solvent may dissolve throttle blade sealant.
- Secondary barrels of a 4-barrel carburetor
- Rear carburetor second barrels of front carburetor of a 2 x 4 setup with progressively opening throttles. (Use in both front rear carburetor primary barrels only on 2 x 4 setups with simultaneously opening throttles.

For Professional Use Only. Not for Retail Sale. WARNING: Cancer - www.P65Warnings.ca.gov.

Top Engine Cleaner - Aerosol



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 32 oz. | 6 | 10-3015 | 19355198 |

PRODUCT DESCRIPTION AND FUNCTION:

Top Engine Cleaner is a professional gasoline intake cleaner formulated to clean the air intake system via a professional pressurized applicator. This product removes harmful carbon buildup in an engine, cleans air intake, air intake plenum, intake manifold and intake values. It helps restore lost power and performance.

It is a more concentrated formula developed specifically for the new generation of high performance engines. The proprietary chemistry was developed to address the premature soot and carbon deposits found in high output, low displacement engines. Can be used in all gasoline powered engines including PFI and GDI (gasoline direct injection).

Recommended use every year, or every 15,000-20,000 miles. One 32 oz. can for severe deposits. A minimum of 16 oz. per induction cleaning service.

For Professional Use Only. Not for Retail Sale.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

- Removes gum, varnish, and carbon to make tough tune-ups easy and long-lasting
- Mixture of solvents, penetrating agents, and lubricating oil helps free sticking valves and sluggish compression rings, and purge excessive deposits from combustion chambers
- Designed to eliminate deposits that may cause rough idle, stalling, hesitation, pings, and engine run-on

Coolant System Fluorescent Tracer Dye



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 1 oz. | 24 | 10-5057 | 12378563 |

PRODUCT DESCRIPTION AND FUNCTION:

Coolant System Fluorescent Tracer Dye is a fluorescent leak detection dye for traditional coolant systems. This fluorescent tracer dye quickly pinpoints the exact location of coolant fluid leaks. It is a safe and easy method that helps eliminate guess work, save labor and speed up service. Coolant System Fluorescent Tracer Dye may also be used to isolate power steering system leaks. Coolant System Fluorescent Tracer Dye can be used with DEX-COOL coolants, but it may change the color of the coolants.

For Professional Use Only. Not for Retail Sale.

PRODUCT FEATURES AND BENEFITS:

- Designed to quickly pinpoint leaks in traditional coolant systems
- Fluorescent dye assists with visual leak detection to eliminate guess work
- Easy method of leak detection to save on labor and speed up service

Coolant System Tracer Dye



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 1 oz. | 6 | 10-5046 | 89022219 |

PRODUCT DESCRIPTION AND FUNCTION:

Coolant System Tracer Dye is a fluorescent leak detection dye that is specifically formulated to pinpoint leak sources in cooling systems that use DEX-COOL (orange) coolants. The use of the Coolant System Tracer Dye will not change the original appearance of the long life coolants. This tracer dye is used in conjunction with the Ultra Violet (UV) Leak Detection Lamp Kit (PN 12377979).

For Professional Use Only. Not for Retail Sale.

PRODUCT FEATURES AND BENEFITS:

- Designed to quickly pinpoint leaks in cooling systems that use DEX-COOL (orange) coolants
- Special formula will not change the color of the coolant
- Fluorescent dye assists with visual leak detection to eliminate quess work

Fluorescent Dye, 4-in-1



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 1 oz. | 24 | 10-5045 | 88861206 |

PRODUCT DESCRIPTION AND FUNCTION:

The 4-in-1 Fluorescent Dye is a multipurpose fluorescent leak detection dye used in conjunction with Ultra Violet (UV) Leak Detection Lamp Kit (PN 12377979) to pinpoint leaks in oil and oil-based fluid systems. The fluorescent dye can be used with gasoline and diesel engine oil, power steering fluid, and automatic transmission fluid. The 4-in-1 Fluorescent Dye can safely remain in the system after work is performed. For Professional Use Only. Not for Retail Sale.

PRODUCT FEATURES AND BENEFITS:

- Multi-purpose dye can be used with gasoline and diesel engine oil, power steering fluid, and automatic transmission fluid
- Specially formulated to safely remain in the system after the leak detection is complete
- Works in conjunction with the Ultra Violet (UV) Leak Detection Lamp Kit (PN 12377979)

Fluorescent Tracer Dye Injector Package (Tool)



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 1 | 1 | 15-91244 | 12344968 |

PRODUCT DESCRIPTION AND FUNCTION:

Fluorescent Tracer Injector Dye Tool injects tracer dye into the air conditioning system for leak detection purposes. This tool is designed for use with R-134a air conditioning systems.

Use with part number 88844127.

For Professional Use Only. Not for Retail Sale.

PRODUCT FEATURES AND BENEFITS:

- Injects dye into your air conditioning system to help pinpoint leaks
 - Specially designed for use with R-134a air conditioning systems

Ultra Violet (UV) Lamp Bulb - 12 Volt DC



| Container Size | Unit Package | ACDelco Part Number | GM Part Number | |
|----------------|--------------|----------------------------|----------------|--|
| Bulb | 1 | 10-105 | 12378176 | |

PRODUCT DESCRIPTION AND FUNCTION:

For use with leak detector ultra-violet lamp kit part number 12377979.

Ultra Violet (UV) Leak Detector Lamp Kit



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| Kit | 1 | 12377979 | 12377979 |

PRODUCT DESCRIPTION AND FUNCTION:

The Ultra Violet (UV) Leak Detector Lamp Kit is used to provide the necessary light conditions to detect fluid leaks when using fluorescent dye in radiator, transmission, steering, or brake systems. Kit sold with UV enhancing glasses.

For Professional Use Only. Not for Retail Sale.

- Provides UV light to detect fluid leaks when using a fluorescent dye
- Can be used with radiator, transmission, steering, or brake system leaks
- Kit includes UV enhancing glasses to assist with visual leak detection



Anti-Seize Lubricant

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 8 oz. | 2 | 10-4067 | 88862477 |

PRODUCT DESCRIPTION AND FUNCTION:

Anti-Seize Lubricant is a product that is applied as a liquid that becomes a dry film. The dry film makes threaded parts easier to install. This product is oxygen sensor safe, non-greasy, and withstands up to 2400°F.

ATE Plastilube Grease



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 75 ml. | 1 | 10-4094 | 19301850 |

PRODUCT DESCRIPTION AND FUNCTION:

ATE Plastilube Grease is an ideal high quality aftermarket replacement component for one or more of the following vehicle systems: engine mechanical, cooling, hvac, automatic transmission/transaxle, manual drivetrain and axles, brakes, steering and suspension, wiper and washer, and/or engine fuel management. This premium aftermarket lubricant is manufactured to meet or exceed your expectations for fit, form, and function.

Brake Caliper Lubricant - Cartridge



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 14 oz. | 1 | 10-4077 | 12377969 |

PRODUCT DESCRIPTION AND FUNCTION:

Provides a water-resistant coating on brake caliper slide surfaces. This product is required to equalize pressure between inner and outer brake pads. With regular use it can help extend brake pad life.

PRODUCT FEATURES AND BENEFITS:

 Recommended for periodic maintenance of medium-duty truck brake caliper.

Chassis Grease - Cartridge



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 14 oz. | 6 | 10-4060 | 12377985 |

PRODUCT DESCRIPTION AND FUNCTION:

Chassis Grease - Cartridge is a premium grease consisting of oil, lithium thickening agents, and special lubricants used for chassis lubrication. This chassis grease is not intended for use as a wheel bearing grease. Chassis Grease - Cartridge is for standard chassis lubrication in all GM vehicles. This product requires a grease gun for application.

PRODUCT FEATURES AND BENEFITS:

- Premium grease consisting of oil, lithium thickening agents, and special lubricants used for chassis lubrication
- Good on all GM chassis lubrication applications
- Water resistant for additional wash-out protection

Dielectric Lubricant



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|-----------------------|
| 2 oz. | 12 | 10-4071 | 12377900 |

PRODUCT DESCRIPTION AND FUNCTION:

Dielectric Lubricant is used to protect electrical terminals from moisture, oxidation, and corrosion. It also eases the assembly of electrical connectors.

PRODUCT FEATURES AND BENEFITS:

- Non-corrosive and oxidation resistant for component protection
- Electrically insulating for use with spark plugs
- Water repellent for moisture protection

Dielectric Silicone Grease



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 1 oz. | 6 | 10-4064 | 12345579 |

PRODUCT DESCRIPTION AND FUNCTION:

Dielectric Silicone Grease is a silica thickened dimethyl silicone fluid. It has a broad temperature range from -65 degrees Fahrenheit to 400 degrees Fahrenheit (-54 degrees Celsius to 204 degrees Celsius). This product is non-corrosive, oxidation resistant, electrically insulating, radiation resistant, chemical resistant, and water repellent. Dielectric Silicone Grease is designed to coat the inside of spark plug boots to prevent them from sticking to ceramic insulators. It also checks corrosion by improving boot seal. Do not apply to silicone rubber components, as the grease will react with and harm that material.

- Non-corrosive and oxidation resistant for component protection
- Electrically insulating for use with spark plugs
- Water repellent for moisture protection



Multi-Purpose Lubricant - Aerosol

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 5.25 oz. | 12 | 10-4040 | 01052948 |

PRODUCT DESCRIPTION AND FUNCTION:

This product has a high load carrying capacity, corrosion properties, and metal-to-metal wear protection. The product starts as a thin liquid that allows it to creep into the smallest spaces, then cures to leave a dry film. The mineral spirit blend, when applied, evaporates to leave a film that will not attract dust, dirt, or grit, and makes it resistant to water. Non-chlorinated, VOC compliant.

E.O.S. Assembly Lubricant



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 16 oz. | 12 | 10-4021 | 88862587 |

PRODUCT DESCRIPTION AND FUNCTION:

E.O.S. (Engine Oil Supplement) Assembly Lubricant is specially formulated as an engine assembly lubricant that helps provide protection against run-in wear and piston scuffing. It also assists in protecting against run-in camshaft lobe and lifter scuffing resulting from insufficient lubrication. This product is not recommended for use as an additive to engine oil.

For Professional Use Only. Not for Retail Sale.

Gear Marking Compound



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 1 oz. | 12 | 10-5055 | 01052351 |

PRODUCT DESCRIPTION AND FUNCTION:

Gear Marking Compound is a dark yellow colored grease that is used to mark ring gear teeth to determine contact points. For Professional Use Only. Not for Retail Sale. WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

PRODUCT FEATURES AND BENEFITS:

- Dark yellow color for high visibility of the compound
- Wide range of applications in a variety of vehicles
- Quality grease used to mark ring gear teeth to determine contact points

High Temperature Grease



| g | | | |
|----------------|--------------|----------------------------|----------------|
| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
| 1.75 oz. | 6 | 10-4048 | 12345996 |

PRODUCT DESCRIPTION AND FUNCTION:

High Temperature Grease is an ivory colored, high temperature grease with a special blend of lithium complex thickening agents, petroleum oils, and special lubricity additives. It is a high quality grease suitable for both medium and high temperature applications. The water-resistant High Temperature Grease is ideal for wheel bearing applications.

PRODUCT FEATURES AND BENEFITS:

- Aides in lubricity for additional anti-wear support
- Additional lubrication helps quiet noisy parts
- Water repellent, including salt water, for additional protection against water washout

Hydraulic Fluid (Aeroshell 41)



| Try at danie T talia (Tiol oblicit TT) | | | | |
|----------------------------------------|--------------|----------------------------|-----------------------|--|
| Container Size | Unit Package | ACDelco Part Number | GM Part Number | |
| 32 oz. | 12 | 10-5041 | 88863458 | |

PRODUCT DESCRIPTION AND FUNCTION:

Hydraulic Fluid (Aeroshell 41) is designed for use in power liftgate systems. The mineral oil based super clean hydraulic fluid features an oxidation inhibitor and a non-zinc anti-wear additive. This hydraulic fluid is dyed red for identification and leak detection purposes. It may be used in hydraulic systems where very low temperature flow properties are desired, synthetic rubber seals are in use, and super clean solid particle contaminant standards are required. This hydraulic fluid is the GM approved fluid for use on 2010+ SRX, CTS, Equinox and Terrain lift-gates. It is not recommended for systems using natural rubber seals.

For Professional Use Only. Not for Retail Sale.

- Includes an oxidation inhibitor to minimize the formation of deposits, varnishes, and sludge from fluid breakdown that can be harmful to vehicle components
- Includes a non-zinc anti-wear additive for lasting protection with additional environmental benefits
- Product has been dyed red for identification and leak detection purposes



Hydraulic Pump Fluid

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 16 oz. | 1 | 10-5056 | 88865214 |

PRODUCT DESCRIPTION AND FUNCTION:

Hydraulic Pump Fluid is designed with oxidation stability, reducing deposit formation and helping to improve pump and valve performance. This hydraulic pump fluid is developed to meet the stringent requirements of severe hydraulic systems using high pressure and high output pumps, as well as handling the critical requirements of other hydraulic system components. This hydraulic pump fluid offers viscosity control over a wide temperature range making it particularly suited for equipment subjected to wide seasonal temperature variations. For Professional Use Only. Not for Retail Sale.

PRODUCT FEATURES AND BENEFITS:

- Superior viscosity control across a wide temperature range of applications
- High rust and corrosion resistance for additional component protection
- Developed to meet stringent requirements of severe hydraulic systems using high pressure and high output pumps

Hydraulic Pump Fluid



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 16.9 fl. oz. | 4 | 10-5075 | 19351694 |

PRODUCT DESCRIPTION AND FUNCTION:

Hydraulic Pump Fluid is a special central hydraulic fluid, formulated with the highest quality base oils, together with a well selected additive package. This formulation helps ensure reduced hiss and crunch noise and provides enhanced machinery protection due to excellent corrosion protection. The favorable viscosity index, together with the low evaporation loss, helps guarantee functional safety over a wide application range.

For Professional Use Only. Not for Retail Sale.

Low Temperature Synthetic Dampening Grease



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 30 cc. | 1 | 10-4098 | 19329355 |

PRODUCT DESCRIPTION AND FUNCTION:

Low Temperature Synthetic Dampening Grease is a PTFE fortified, silica thickened, light viscosity, synthetic hydrocarbon grease intended for mechanical components requiring a light amount of damping.

M-77 Paste



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 2 oz. | 6 | 10-4114 | 19356408 |

PRODUCT DESCRIPTION AND FUNCTION:

M-77 Paste is a solid lubricant paste with silicone carrier oil. It is:

- Suitable for lubrication points with low to moderate loads and low speeds which are subjected to water and extreme temperatures. At temperatures above 230°C (446°F), the carrier volatilizes leaving virtually no residue, and the remaining dry sliding film itself takes over the lubrication up to +400°C (+662°F).
- Suitable for lubricating parts consisting of materials that are not resistant to mineral oils.
- Used successfully on metal/metal combinations with frictional and contact surfaces, brake anchor plates and the brake pistons of disc brakes.

Instructions: Clean the contact areas and apply with brush, spatula, grease gun or automatic lubricating device. Can be used in central lubricating systems.

Moisture Displacing Lubricant - Aerosol



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 12 oz. | 12 | 10-4045 | 88862629 |

PRODUCT DESCRIPTION AND FUNCTION:

Moisture Displacing Lubricant is a special lubricant used to help displace moisture for mechanical, electrical, metal, fabric, rubber, or synthetic materials. It also quiets squeaks and penetrates rust to free nuts and bolts. This product is a clear, clean lubricant with excellent corrosion protection properties. Moisture Displacing Lubricant is Volatile Organic Compound (VOC) compliant.

- Product has wide application for a variety of vehicle systems and components
- Effective in such areas as carburetor linkage, ignition, wiring, spark plugs, alternators, windshield wiper motors and linkage, antenna mast and mechanism, heater, air conditioner and other accessory power controls, hinges, connector terminals, interior or exterior hardware, and V-belts
- · Helps lubricate and prevent freezing in door locks



Molykote CU-7439

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 2 gr. | 1 | 10-4096 | 19303310 |

PRODUCT DESCRIPTION AND FUNCTION:

Molykote Cu-7439 is a long term lubricant for machine components that are exposed to high loads, high temperatures and corrosive environments. The paste exhibits excellent adhesion to metal surfaces, providing not only good resistance to removal by steam and/or hot water, but increased protection from corrosion.

Multi-Purpose Grease (Aerosol)



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 11 oz. | 6 | 10-4038 | 89021668 |

PRODUCT DESCRIPTION AND FUNCTION:

Multi-Purpose Grease is a light-colored, medium density, grease type lubricant. It sprays like a fluid and gels to a grease. Multi-Purpose Grease has a high level of water and acid resistance. It is excellent in close tolerance situations where no grease fittings exists. Multi-Purpose Grease will not dry up and it resists temperatures up to 265 degrees Fahrenheit. This product can be applied to hood and truck releases, latches, striker plates, ash tray slides, door hinges and locks, cables and battery terminals, and other mechanical devices. This product is not for sale in the State of California due to state regulations.

For Professional Use Only. Not for Retail Sale.

PRODUCT FEATURES AND BENEFITS:

- Water repellent for additional protection against water washout
- Resists rust and corrosion for additional component protection
- Adds additional lubrication to help eliminate annoying squeaks

Multi-Purpose Lubricant with PTFE - Cartridge



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 14 oz. | 1 | 10-4072 | 89022180 |

PRODUCT DESCRIPTION AND FUNCTION:

Multi-Purpose Lubricant with PTFE is intended for wide temperature lubrication of bearings, sliding surfaces, and small gear trains. It is formulated with PTFE (polytetrafluoroethylene), a synthetic polymer that is non-reactive and deals extremely well with corrosive chemicals. This product is compatible with most ester-vulnerable plastics and polymers.

For Professional Use Only. Not for Retail Sale.

PRODUCT FEATURES AND BENEFITS:

- PTFE filler helps provide improved lubricity and low temperature starting torque
- Compatible with most ester-vulnerable plastics and polymers
- Intended for wide temperature lubrication of bearings, sliding surfaces, and small gear trains

Nickel Anti-Seize Lubricant



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|----------------------------|-----------------------|
| 8 oz. | 12 | 10-4039 | 12371386 |

PRODUCT DESCRIPTION AND FUNCTION:

Nickel Anti-Seize Lubricant is a high temperature, high quality, heavy duty, lead-free lubricant that resists galling and corrosion and reduces wear in heavy pressure applications. It is recommended for use where copper contamination must be avoided. This product also performs well under conditions of extreme pressure and temperature. Nickel Anti-Seize Lubricant is designed specifically for use with stainless steel, titanium, and nickel alloys. This product should not be used on oxygen sensors.

WARNING: Cancer - www.P65Warnings.ca.gov.

PRODUCT FEATURES AND BENEFITS:

- Contains tenacious metals, oils, and graphite materials that cannot be burned away or removed by slow moving parts
- Protects threaded fasteners and fittings from heat, freezing, seizure, or galling at temperatures from -65°F to 2,400°F
- May be used on pumps, sensors, valves, nuts, and bolts where extreme conditions of heat exist

P-80 Fmulsion Temporary Rubber Assembly Lubricant



| To Emaioron formporary massor recombly Eastroant | | | | |
|--------------------------------------------------|--------------|---------------------|----------------|--|
| Container Size | Unit Package | ACDelco Part Number | GM Part Number | |
| 10 ml. | 1 | 10-4095 | 19303123 | |

PRODUCT DESCRIPTION AND FUNCTION:

P-80 Emulsion Temporary Rubber Assembly Lubricant is biodegradable, alcohol-free, petroleum distillate-free, silicone-free and is compatible with most natural and synthetic rubbers, metals, and plastics. It can be used to ease installation of seals, bushings, grommets, hoses, o-rings, grips and other parts.

PRODUCT FEATURES AND BENEFITS:

Keep container closed when not in use



PTFE Grease-High Viscosity

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 2 oz. | 1 | 10-4103 | 19333360 |

PRODUCT DESCRIPTION AND FUNCTION:

PTFE Grease-High Viscosity is a PTFE-thickened, heavy viscosity dimethyl silicone grease with excellent water resistance and mechanical stability under a wide temperature range.

PTU Synthetic Lubricant GL-5 (75W-90)



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 32 fl. oz. | 12 | 10-4105 | 19351882 |

PRODUCT DESCRIPTION AND FUNCTION:

PTU Synthetic Lubricant is an enhanced, specially formulated, full synthetic GL-5 75W-90 hypoid gear lubricant. It helps provide improved performance.

Rear Differential Clutch Fluid GL-4 (75W-90)



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|-----------------------|
| 1 L. | 1 | 10-4070 | 88863349 |

PRODUCT DESCRIPTION AND FUNCTION:

Rear Differential Clutch Fluid, 75W-90 GL-4 is a long-life, partial synthetic oil. It is specifically designed to prevent the development of layers on the clutch plates, allowing the clutch to function problem-free over extended periods. This product is for use only in vehicles with a model year 2009+ Haldex limited slip coupling. It is for application in Haldex wet clutches with sinter and organic plates.

PRODUCT FEATURES AND BENEFITS:

- Engineered with specialized friction characteristics: prevents clutch stick slip, protects against corrosion, and provides excellent lube and shear performance
- All-climate fluid that manages temperatures as low as -22 degrees Fahrenheit (-30 degrees Celsius) to as high as 284 degrees Fahrenheit (140 degrees Celsius)
- Specifically formulated for use in vehicles with a model year 2009+ Haldex limited slip coupling

Rubber Lubricant



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 3.8 oz. | 1 | 10-4111 | 19354433 |

PRODUCT DESCRIPTION AND FUNCTION:

Rubber Lubricant is a quick-drying, water-based surfactant mixture that dries tacky to help parts stay in place. It has been specially formulated to not dry, crack or otherwise harm rubber parts. Instructions: Apply just enough ACDelco Rubber Lubricant to create a thin film of lubricant on the rubber or plastic part. This can be done manually or automatically with a bath, dip, brush, spray, sponge, or squirt technique. Apply more if the film dries before installation is complete.

Avoid extended contact with uncured paint, zinc, aluminum, cold rolled steel, or copper and its alloys. May craze polycarbonate, polymethyl methacrylate, and polyphenylene oxide.

Rubber Lubricant



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 5 gal. | 1 | 10-4078 | 12345884 |

PRODUCT DESCRIPTION AND FUNCTION:

An odorless, slightly viscous clear liquid specifically formulated to meet GM rubber lubrication requirements. It is suited for use as a lubricant in any manual or automatic tire-mounting operation. The material is water-based and any residues can be rinsed off with tap water.



Silicone Brake Lubricant

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 8 oz. | 12 | 10-4019 | 88862182 |

PRODUCT DESCRIPTION AND FUNCTION:

Silicone Brake Lubricant is a silicone fluid-based, grease-like material specially blended with fine thermally conductive metal oxide powders. This formulation results in high thermal conductivity, low bleed and high temperature stability. This highly viscous product will not harden, melt or dry out and will adhere to metal surfaces even when exposed to high temperatures for extended periods of time. WARNING: Cancer - www.P65Warnings.ca.gov.

PRODUCT FEATURES AND BENEFITS:

- Formulated with PTFE for longer lubricant life and lower levels of friction
- Lubrication properties reduce noise from brake vibration
- Lubricant is compatible with most rubber and plastic compounds

Silicone Dielectric Grease



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 1 oz. | 6 | 10-4083 | 19260901 |

PRODUCT DESCRIPTION AND FUNCTION:

Silicone Dielectric Grease is designed primarily for automotive spark plug boots and electrical connectors. The grease may also be used as a seal and lubricant for cable connectors, battery terminals, rubber door seals, and plastic O-rings. Silicone Dielectric Grease is a polytetrafluoroethylene (PTFE) thickening silicone grease that has a broad temperature range (-40 degrees Fahrenheit to 392 degrees Fahrenheit/-40 degrees Celsius to 200 degrees Celsius), excellent dielectric strength, is oxidation resistance, water repellent, non-corrosive, chemically inert (except towards silicone rubber), and has a long shelf life. Do not apply to silicone rubber components, as the grease will react with and harm that material

PRODUCT FEATURES AND BENEFITS:

- Excellent dielectric strength for use with spark plugs, battery terminals, and other electrical connectors
- Non-corrosive and oxidation resistant for additional component protection
- Water repellent for moisture protection

Super Lube® with PTFE - Aerosol



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 11 oz. | 12 | 12346241 | 12346241 |

PRODUCT DESCRIPTION AND FUNCTION:

Super Lube® is a synthetic, multi-purpose, heavy duty lubricant that is compatible with most other lubricants. It helps to prevent rust and corrosion while reducing friction. This super lube has high dielectric strength, will not drip or run, and is water resistant. Super Lube® is temporarily thinned with a solvent that cleans and penetrates the components to be lubricated, carrying the product to those components. After a short time, the product leaves behind a thin film of grease that provides long term lubrication and does not evaporate, dry, or wash out. Super Lube® comes in an aerosol can for easy application.

PRODUCT FEATURES AND BENEFITS:

- Synthetic-based lubricant that outlasts petroleum-based lubricants
- Multi-surface product that can be used on metal, rubber, and plastics
- Easy to apply sprays as a liquid and gels to a grease

Super Lube® with PTFE



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 3 oz. | 6 | 10-4057 | 12371287 |

PRODUCT DESCRIPTION AND FUNCTION:

Super Lube® with PTFE (polytetrafluoroethylene) is a synthetic, multi-purpose, heavy duty lubricant that is compatible with most other lubricants. It helps to prevent rust and corrosion while reducing friction. This Super Lube® has high dielectric strength, will not drip or run, and is water resistant. Super Lube® with PTFE is a synthetic polymer that is non-reactive and deals extremely well with corrosive chemicals. This product comes in a tube for easy pinpoint application.

PRODUCT FEATURES AND BENEFITS:

- Synthetic-based lubricant that outlasts petroleum-based lubricants
- Multi-surface product that can be used on metal, rubber, and plastics
- Product is temperature resistant and remains free flowing in freezing temperatures

Supercharger Oil



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 4 oz. | 12 | 10-4041 | 12345982 |

PRODUCT DESCRIPTION AND FUNCTION:

Supercharger Oil is a high quality fluid that is used to help keep supercharger bearings operating properly. It is for use with all supercharged vehicles. Supercharger Oil meets or exceeds GM OE specifications.



Synthetic Multi-Purpose Lubricant

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 1.75 oz. | 1 | 10-4066 | 88861426 |

PRODUCT DESCRIPTION AND FUNCTION:

Synthetic Multi-Purpose Lubricant provides excellent anti-wear and pressure protection. This product is used for lubricating the actuator rod knob and base assembly for model year 2007 and later GMC Acadia and Saturn Outlook and 2008 model year and later Buick Enclave.

PRODUCT FEATURES AND BENEFITS:

- · Provides excellent anti-wear and pressure protection
- High-quality formulas to help keep your vehicle's components running smoothly



Synthetic Grease

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 1 lb. | 1 | 10-4063 | 19257121 |

PRODUCT DESCRIPTION AND FUNCTION:

Synthetic Grease is intended for transmission slip yoke applications. It has excellent shear stability, load carrying capacity, and ferrous corrosion protection. This product is also water-resistant. Use Synthetic Grease only on two wheel drive vehicles with four speed automatic transmissions. Do not use on two wheel drive vehicles with six speed transmissions or any four wheel drive vehicles. WARNING: Cancer - www.P65Warnings.ca.gov.

PRODUCT FEATURES AND BENEFITS:

- Water-resistant lubricant specially designed for transmission slip yoke applications
- Excellent shear stability, load carrying capacity, and ferrous corrosion protection
- High-quality formulas to help keep your vehicle's components running smoothly



Weatherstrip Lubricant

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 1 oz. | 1 | 10-4074 | 03634770 |

PRODUCT DESCRIPTION AND FUNCTION:

Weatherstrip Lubricant can be used in many automotive applications to help reduce squeaks and rattles. This easily applied lubricant has a low evaporation rate, is insoluble in all common solvents, and does not react with paint or adhesives. It is non-flammable, odorless, and colorless

PRODUCT FEATURES AND BENEFITS:

- Formulated for a wide range of applications, including, fans, clutch bearings, convertible top seals, front and sliding door seals, T-Top weatherstripping
- Easily applied lubricant has a low evaporation rate, is insoluble in all common solvents, and does not react with paint or adhesives
- Multi-purpose lubricant is non-flammable, odorless, and colorless



Wheel Bearing and Chassis Lubricant

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 14 oz. | 12 | 10-4042 | 01051344 |

PRODUCT DESCRIPTION AND FUNCTION:

Wheel Bearing and Chassis Lubricant is intended primarily for lubrication of front wheel bearings. It is a special blend of lithium complex thickening agents, oils, and lubrication additives. This product is suitable for both medium- and high-temperature applications and has good water washout resistance.

PRODUCT FEATURES AND BENEFITS:

- This product is certified to the highest performance classifications (GC-LB) of the NLGI (National Lubricating Grease Institute) for both chassis and wheel bearing lubrication
- Blend of lithium complex thickening agents, oils, and lubrication additives is intended for lubrication of front wheel bearings
- Suitable for both medium- and high-temperatures applications



Wheel Speed Sensor Anti-Corrosion Grease

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 3 oz. | 1 | 10-4116 | 19366880 |



PRODUCT DESCRIPTION AND FUNCTION:

Wheel Speed Sensor Anti-Corrosion Grease is a calcium sulfonate complex grease that is part of a new generation of lubrication grease technology. This product performs over a wide temperature range, exhibits good shear stability, possesses water resistance properties, provides protection against rust and corrosion, and possesses good anti-wear and load carrying abilities.

For Professional Use Only. Not for Retail Sale.

dexos2™ 5W-30



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|-----------------------|
| 32 oz. | 12 | 10-9129 | 19354306 |

PRODUCT DESCRIPTION AND FUNCTION:

dexos 2^{TM} 5W-30 synthetic engine oil can be used in new and older GM vehicles where the recommended viscosity grade is SAE 5W-30. It is fully back-serviceable in older engines.



Four-in-One Assortment Kit

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| Kit | 1 | 19368258 | 19368258 |

PRODUCT DESCRIPTION AND FUNCTION:

The Touch-Up Paint Assortment Kit includes six of the top selling paints (four units of each) and the touch-up paint rack (part number 1234668).

PRODUCT FEATURES AND BENEFITS:

Touch-up paint includes:

Black: 19367651 Summit White: 19367652 Iridium Metallic: 19367759 Switchblade Silver Metallic: 19367653 Limited Addiction Red: 19367663 White Diamond: 19367784





| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|-----------------------|--------------|---------------------|----------------|
| 24" h x 7" w x 5.5" d | 1 | 12346668 | 12346668 |

PRODUCT DESCRIPTION AND FUNCTION:

The Four-in-One Paint Rack is a metal rack that holds 24 four-in-one touch-up paint tools.

High Gloss Black Engine Enamel Paint - Aerosol



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 11 oz. | 6 | N/A | 89021940 |

PRODUCT DESCRIPTION AND FUNCTION:

High Gloss Black Aerosol Engine Enamel Paint covers engine components in a protective enamel coat with a high gloss black finish. The high gloss enamel reflects light to achieve a high-shine finish that is also easy to clean. Specially designed for rust protection on engine components, High Gloss Black Aerosol Engine Enamel Paint can also be used for moisture protection on transmissions, motors, boilers, furnaces, and other at-risk equipment. This product can be applied to engines, transmissions, motors, and other equipment, but is not intended for high heat exhaust components, headers, mufflers, or tailpipes.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

PRODUCT FEATURES AND BENEFITS:

- Fast drying formula is tack free in 5 minutes, has a hard film in 10 minutes, and is dry to the touch in 30 minutes after application
- Formulated without CFC chemicals to be more environmentally friendly
- Resists temperatures up to 500 degrees Fahrenheit. The paint not only remains intact during average engine temperatures and beyond, but the heat actually cures the paint to the components and creates a lasting bond

Low Gloss Black Engine Enamel Paint - Aerosol



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 11 oz. | 6 | N/A | 89021939 |

PRODUCT DESCRIPTION AND FUNCTION:

Low Gloss Black Aerosol Engine Enamel Paint covers engine components in a protective enamel coat with a matte black finish. The low gloss finish is perfect for hiding irregularities or imperfections due to its low sheen, though still retaining the easy cleaning capabilities of a glossier finish. Specially designed for rust protection on engine components, Low Gloss Black Aerosol Engine Enamel Paint can also be used for moisture protection on transmissions, motors, boilers, furnaces, and other at-risk equipment. This product is not intended for high heat exhaust components, headers, mufflers, or tailpipes. WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

PRODUCT FEATURES AND BENEFITS:

- Fast drying formula is tack free in 5 minutes, has a hard film in 10 minutes, and is dry to the touch in 30 minutes after application
- Formulated without CFC chemicals to be more environmentally friendly
- Resists temperatures up to 500 degrees Fahrenheit. The paint not only remains intact during average engine temperatures and beyond, but the heat actually cures the paint to the components and creates a lasting bond

Reconditioning Paint (Black/Aqua) - Aerosol



| 1000114111911119 1 41111 (214010714444) 71010001 | | | | | |
|--------------------------------------------------|--------------|----------------------------|----------------|--|--|
| Container Size | Unit Package | ACDelco Part Number | GM Part Number | | |
| 13 oz. | 6 | 10-7012 | 01051499 | | |

PRODUCT DESCRIPTION AND FUNCTION:

Reconditioning Paint is designed with a quality formula that features a black and aqua speckled finish. Reconditioning Paint has excellent adhesion, is fast drying and does not bubble, blush, or lift. Perfect for use during reconditioning or repair projects, Reconditioning Paint is designed to match OEM trunk paint.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

PRODUCT FEATURES AND BENEFITS:

- The correct speckled finish matches GM Original Equipment speckled trunk paint
- Easy to use aerosol can allows for ease of application and an even coating every time
- Appropriate for use on various surfaces and it can be applied to bare metal or previously coated surfaces

Reconditioning Paint (Gray/White) - Aerosol



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 13 oz. | 6 | 10-7011 | 01051498 |

PRODUCT DESCRIPTION AND FUNCTION:

Reconditioning Paint is designed with a quality formula that features a gray and white speckled finish. Reconditioning Paint has excellent adhesion, is fast drying and does not bubble, blush or lift. Perfect for use during reconditioning or repair projects, Reconditioning Paint is designed to match OEM trunk paint.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

- The correct speckled finish matches GM Original Equipment speckled trunk paint
- Easy to use aerosol can allows for ease of application and an even coating every time
- Appropriate for use on various surfaces and it can be applied to bare metal or previously coated surfaces



Cold Climate Power Steering Fluid

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 16 oz. | 12 | 10-5043 | 12345866 |

PRODUCT DESCRIPTION AND FUNCTION:

A partially synthetic fluid with exceptional low-temperature properties and increased oxidation stability, Cold Climate Power Steering Fluid is specially designed for use in vehicles equipped with rack-and-pinion power steering systems and it offers superior protection for your power steering system when operating in extreme cold climate conditions where temperatures reach below-20 degrees Fahrenheit.

PRODUCT FEATURES AND BENEFITS:

- Inhibits corrosion and is non-foaming, providing additional protection against unwanted wear in the power steering system
- Minimizes pump squeal for quieter ride
- Low temperature fluidity to improve power steering response in cold weather

Cold Climate Power Steering Fluid



Container SizeUnit PackageACDelco Part NumberGM Part Number32 oz.1210-504412345867

PRODUCT DESCRIPTION AND FUNCTION:

A partially synthetic fluid with exceptional low-temperature properties and increased oxidation stability, Cold Climate Power Steering Fluid is specially designed for use in vehicles equipped with rack-and-pinion power steering systems and it offers superior protection for your power steering system when operating in extreme cold climate conditions where temperatures reach below-20 degrees Fahrenheit.

PRODUCT FEATURES AND BENEFITS:

- Inhibits corrosion and is non-foaming, providing additional protection against unwanted wear in the power steering system
- · Minimizes pump squeal for quieter ride
- Low temperature fluidity to improve power steering response in cold weather

Electro-Hydraulic Power Steering Fluid



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 33.8 oz. | 6 | 10-5050 | 88901975 |

PRODUCT DESCRIPTION AND FUNCTION:

Synthetic oil for central hydraulic systems, level control, hydro pneumatic suspension, shock absorber, and power steering.

PRODUCT FEATURES AND BENEFITS:

 Product should not be mixed with CHF 7.1 or any other hydraulic oil

Power Steering Fluid



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 32 oz. | 12 | 10-5073 | 19329448 |

PRODUCT DESCRIPTION AND FUNCTION:

An amber-colored, light-bodied mineral oil, Power Steering Fluid contains a specially developed additive package to provide excellent performance in power steering systems. Expertly designed for use in any season, Power Steering Fluid is approved for year-round use for most customers.

PRODUCT FEATURES AND BENEFITS:

- Advanced additive package for excellent performance
- Reduces power-steering related noise, resulting in a quieter passenger compartment
- Special formula is non-foaming and anti-corrosive for longer fluid life and protection for power steering system components

Power Steering Fluid



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 16 oz. | 12 | 10-5074 | 19329450 |

PRODUCT DESCRIPTION AND FUNCTION:

An amber-colored, light-bodied mineral oil, Power Steering Fluid contains a specially developed additive package to provide excellent performance in power steering systems. Expertly designed for use in any season, Power Steering Fluid is approved for year-round use for most customers.

- Advanced additive package for excellent performance
- Reduces power-steering related noise, resulting in a quieter passenger compartment
- Special formula is non-foaming and anti-corrosive for longer fluid life and protection for power steering system components



Anti-Corrosion Wax Sealant

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 8 oz. | 1 | 10-2027 | 19355725 |

PRODUCT DESCRIPTION AND FUNCTION:

Anti-Corrosion Wax Sealant is a water-based cavity wax with excellent flow ability and outstanding protection against rust and corrosion. This air-drying product is easy to apply with enclosed brush

Instructions: Shake well before use, apply product with brush supplied, clean brush after each use. Air-drying product, reseal can immediately after use to avoid damage to product. Store between +15 and +32 C. Do not expose to extreme heat or cold.

Flange Sealant



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 2.87 oz. | 1 | 10-2017 | 88861422 |

PRODUCT DESCRIPTION AND FUNCTION:

Flange Sealant is ideally suited for use as a gasket dressing. It is a non-setting and non-hardening compound with resistance to joint vibration, shock and thermal expansion. It is resistant to most automotive fluids. It is a non-slump thixotropic gel designed to seal close fitting flanges against most lubricants and automotive fluids. It is designed to fill and seal all surface imperfections in the flange surfaces.

Gasket Maker Sealant



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 1.69 oz. | 6 | 10-2022 | 19333510 |

PRODUCT DESCRIPTION AND FUNCTION:

Gasket Maker is a single component, medium strength, thixotropic, anaerobic sealant that cures when confined between close fitting metal surfaces. It provides an instant low pressure seal and can be used with or without pre-cut, pre-formed gaskets.

PRODUCT FEATURES AND BENEFITS:

- Multi-surface product that adheres well to: aluminum, steel, iron, and magnesium
- Low to high temperature product effective from -58 degrees Fahrenheit to 300 degrees Fahrenheit (-50 degrees Celsius to 149 degrees Celsius)
- Non-corrosive, form-in-place, anaerobic compound that cures instantly when confined

Gasket Sealing Compound



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 16 oz. | 12 | 10-2018 | 01050026 |

PRODUCT DESCRIPTION AND FUNCTION:

Gasket Sealing Compound is a universal sealant used by the automotive, trucking, marine, and aviation industries. It does not harden or dry out and helps extend the life of all gasket materials. This product is designed to provide a strong seal against compression, water, antifreeze, oil, gasoline, pressure, and vacuum leaks. It also helps prevent corrosion of bolt, stud, and fitting threads. For Professional Use Only. Not for Retail Sale.

PRODUCT FEATURES AND BENEFITS:

- Universal sealant used by the automotive, trucking, marine, and aviation industries
- Low to high temperature product that withstands temperatures of -50°F to 400°F
- Designed to provide a strong seal against compression, water, antifreeze, oil, gasoline, pressure, and vacuum leaks

High-Strength, High-Temperature Threadlocker - Red



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|----------------------------|----------------|
| 20 oz. | 1 | 10-1021 | 19332211 |

PRODUCT DESCRIPTION AND FUNCTION:

ACDelco High-Strength, High-Temperature Threadlocker – Red is designed for the permanent locking and sealing of threaded fasteners. The product cures when confined in the absence of air between close fitting metal surfaces and prevents loosening and leakage from shock and vibration. Typical applications include the locking and sealing of large bolts and studs (M25 and larger).

For Professional Use Only. Not for Retail Sale.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.



IMAGE

SOON

Medium Body Seam Sealing Compound

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 10.1 oz. | 12 | 10-2013 | 12378500 |

PRODUCT DESCRIPTION AND FUNCTION:

Medium Body Seam-Sealing Compound is a high performance seam and joint sealer with excellent adhesion to most surfaces. It is water resistant, stays permanently flexible, and withstands weathering, oxidation, salt water, gasoline, and most solvents. This product is safe to use on automotive paint. Medium Body Seam-Sealing Compound should not be applied near catalytic convertors and mufflers, due to extreme heat conditions.

For Professional Use Only. Not for Retail Sale.

WARNING: Reproductive Harm - www.P65Warnings.ca.gov.

PRODUCT FEATURES AND BENEFITS:

- Fast curing and skins over quickly—can be painted 60 minutes after application
- Can be used for all sealing and adhesive applications with a standard caulking gun in both vertical and horizontal joints
- Flexible, non-staining, and non-sagging product that will not crack or shrink



Medium Strength Threadlocker - Blue

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 20 oz. | 6 | 10-2023 | 19333511 |

PRODUCT DESCRIPTION AND FUNCTION:

Medium Threadlocker - Blue is an anaerobic compound designed for locking threaded fasteners that require disassembly with standard hand tools. It performs on aluminum, steel, plated parts, stainless steel, and special alloy parts where shock and vibration may cause fastener to loosen.

PRODUCT FEATURES AND BENEFITS:

- · Successfully converts ordinary fasteners into self-locking, self-sealing fasteners, which helps to eliminate vibration issues, prevent loosening of nuts, bolts, screws, and fittings, keep threads from rusting, seal out corrosion, and prevent air, oil, and fuel leakage
- Designed for easy application—simple to adjust or disassemble, does not cure outside of the joint, and has thixotropic fluid that does not drip from applied area during assembly
- Low to high temperature product effective temperature range is 65 degrees Fahrenheit (-54 degrees Celsius) to 300 degrees Fahrenheit (149 degrees Celsius)



RTV Flange Sealant 5970

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 300 mL | 1 | 10-2020 | 19330905 |

PRODUCT DESCRIPTION AND FUNCTION:

RTV Flange Sealant 5970 has been designed specifically for gasketing applications. It withstands online, low pressure tests carried out before product begins to cure. Typical applications include stamped sheet metal covers (timing covers and oil sumps) where good oil resistance and the ability to withstand high joint movement is

For Professional Use Only. Not for Retail Sale. WARNING: Cancer - www.P65Warnings.ca.gov.



RTV Pink Flange Sealant

| Container Size | Unit Package | ACDelco Part Number | GM Part Number | |
|----------------|--------------|---------------------|----------------|--|
| 10 oz. | 1 | 10-2028 | 19367029 | |



PRODUCT DESCRIPTION AND FUNCTION:

RTV Pink Flange Sealant is a room temperature vulcanizing (RTV) sealant used where good oil resistance and the ability to withstand high joint-movement is required. This product has excellent resistance to automotive engine oils. This product is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected as a sealant for chlorine or other strong oxidizing materials.

RTV Silicone Sealant - Cartridge



| Container Size | Unit Package | ACDelco Part Number | GM Part Number | |
|----------------|--------------|----------------------------|-----------------------|--|
| 5.3 oz. | 6 | 10-2010 | 12378521 | |

PRODUCT DESCRIPTION AND FUNCTION:

RTV Silicone Sealant is a one-component, room-temperature vulcanizing (RTV) sealant. It is a high viscosity engine sealant that cures when exposed to air. The cured material has superior adhesion and elongation properties and is effective even on large gaps. It is very resistant to engine oils and coolants, will not corrode metals, and is blow-out resistant. This silicone sealant is also oxygen sensor safe. This product comes in a cartridge for easy, large-scale application and requires a conventional caulking gun.

WARNING: Reproductive Harm - www.P65Warnings.ca.gov.

- · Engineered for use on a variety of engine components effective on: oil pan, ladder frame, front and rear covers, t-joints, manifold corners, intake, manifold end seals, and cam covers
- Designed for quick and easy application, assembly may be filled with oil or coolant immediately after applying sealant and torqueing the bolts
- · High viscosity product that cures when exposed to air



RTV Silicone Sealant - Tube

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 2.65 oz. | 6 | 10-2006 | 88864346 |

PRODUCT DESCRIPTION AND FUNCTION:

RTV Silicone Sealant is a one-component, room-temperature vulcanizing (RTV) sealant. It is a high viscosity engine sealant that cures when exposed to air. The cured material has superior adhesion and elongation properties and is effective even on large gaps. It is very resistant to engine oils and coolants, will not corrode metals, and is blow-out resistant. This silicone sealant is also oxygen sensor safe. This product comes in a tube for easy, pinpoint application. WARNING: Reproductive Harm - www.P65Warnings.ca.gov.

PRODUCT FEATURES AND BENEFITS:

- Engineered for use on a variety of engine components effective on: oil pan, ladder frame, front and rear covers, t-joints, manifold corners, intake, manifold end seals, and cam covers
- Designed for quick and easy application, assembly may be filled with oil or coolant immediately after applying sealant and torqueing the bolts
- · High viscosity product that cures when exposed to air



RTV Heavy Body Silicone Sealant - Cartridge

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 5 oz. | 6 | 10-2025 | 19333513 |

PRODUCT DESCRIPTION AND FUNCTION:

RTV Heavy Body Silicone Sealant is a one-part neutral cure silicone sealant with a high temperature resistance that cures in the presence of atmospheric moisture to produce a durable and flexible silicone rubber compound. This product provides a long-lasting, flexible seal with excellent adhesion to most surfaces. It retains its elastomeric properties at temperatures from -75°F to 500°F (-60°C to 260°C). WARNING: Cancer - www.P65Warnings.ca.gov.

PRODUCT FEATURES AND BENEFITS:

 Special Precautions: Not recommended for axle and engine applications.



RTV Silicone Sealant - Red - Tube

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 2.8 oz. | 6 | 10-2019 | 12378478 |

PRODUCT DESCRIPTION AND FUNCTION:

RTV (Room Temperature Vulcanizing) Silicone Sealant - Red is a highly effective sealant that adheres to a variety of substances including glass and most metals. It utilizes a non-acid curing system, is non-corrosive to ferrous metals, and resists elevated temperatures. This product is highly resistant to hot gear oil and resists synthetic axle lubricants. RTV Silicone Sealant - Red is highly recommended for all axle sealing applications, however, it is not for use in engine applications. The vehicle should sit for a minimum of one hour after application before extended operations. The silicone will be fully cured in 24 hours.

WARNING: Reproductive Harm - www.P65Warnings.ca.gov.

PRODUCT FEATURES AND BENEFITS:

- Highly effective sealant that adheres to a variety of materials including glass and most metals
- Non-acid curing system, is non-corrosive to ferrous metals, and resists elevated temperatures
- Highly resistant to hot gear oil and resists synthetic axle lubricants



RTV Silicone Sealant - RTV 5900 - Power Can

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|-----------------------|
| 4 oz. | 1 | 10-2014 | 12378479 |

PRODUCT DESCRIPTION AND FUNCTION:

RTV (Room Temperature Vulcanizing) Silicone Sealant - RTV 5900 is a heavy bodied instant sealant. It resists most fluids and offers immediate pressure resistance. This product is also oxygen sensor safe. It is not recommended for engine or axle applications and should not be used on parts in contact with gasoline. This product comes in a pressurized power can for quick and easy application over wide areas. WARNING: Cancer - www.P65Warnings.ca.gov.

PRODUCT FEATURES AND BENEFITS:

- Heavy bodied instant sealant that resists most fluids and offers immediate pressure resistance
- Product distributed in a pressurized power can for quick and easy application over wide areas



RTV Sealant

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 10.3 oz. | 1 | 10-2012 | 19245469 |

PRODUCT DESCRIPTION AND FUNCTION:

This product is a one-part, room temperature curing (RTV) acrylic-based sealant. After curing, the sealant becomes a rubber-like elastic body excelling in heat resistance, cold resistance, and oil resistance. The heat and cold resistance ensures satisfactory rubber-like elasticity in a wide range from 86°F to 302°F. It is a paintable type of sealant suitable for sealing areas of parts to be painted after the parts are assembled.



RTV Silicone Sealant

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 3 oz. | 1 | 10-2011 | 89020326 |

PRODUCT DESCRIPTION AND FUNCTION:

Silicone Sealant is a one-part, room temperature vulcanized (RTV) silicone commonly used as a formed-in-place gasket. It is characterized by good elasticity and temperature and chemical resistance after curing. This product has good automatic transmission fluid resistance. It is not recommended for engine applications.

PRODUCT FEATURES AND BENEFITS:

- One-part, room temperature vulcanized (RTV) silicone commonly used as a formed-in-place gasket
- Characterized by good elasticity and temperature, as well as good chemical resistance after curing
- Good automatic transmission fluid resistance



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 300 mL | 1 | 10-2026 | 19353382 |

PRODUCT DESCRIPTION AND FUNCTION:

Sealant cures on exposure to moisture in the air to form a tough, flexible, silicone rubber gasket. It is designed to provide reliable "formed-in-place" gaskets for mechanical assemblies. It has been designed specifically for production applications where "Blow Out Tests" are required. Sealant resists aging, weathering and thermal cycling without hardening, shrinking or cracking. Typical applications include oil pans, transmission pans, valve covers, valves and guides, timing gear covers, and differential covers. This product is typically used in applications with an operating range of -54 °C to 232 °C. NOTE: Not recommended for parts in contact with gasoline. For Professional Use Only. Not for Retail Sale.

Thread Sealant - Tube



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 1.69 oz. | 6 | 10-2024 | 19333512 |

PRODUCT DESCRIPTION AND FUNCTION:

Thread Sealant is an anaerobic thread sealing and thread locking compound for pipe fittings. It is designed to allow disassembly with standard hand tools. This product performs on aluminum, steel, plated and brass. It exhibits good temperature and solvent resistance. It will seal and lock pipe thread fittings and components. The cure speed is dependent on temperature and substrates. Typical full cure in 72 hours.

- Multi-application product, locking against vibrational loosening in air conditioning, brake line, and fuel line systems
- Excellent lubrication properties for quick and easy assembly and disassembly
- Low to high temperature pipe sealant effective temperature range is -65 degrees Fahrenheit (-54 degrees Celsius) to 300 degrees Fahrenheit (149 degrees Celsius)



Automatic Transmission Fluid

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 32 oz. | 12 | 10-4056 | 22717466 |

PRODUCT DESCRIPTION AND FUNCTION:

Automatic Transmission Fluid contains additives that prolong the life of transmission components and is specially formulated for a long life-span between automatic transmission fluid changes. For GM vehicles, this fluid is intended for Z1 transmissions with codes MJ7 and MJ8.

WARNING: Cancer - www.P65Warnings.ca.gov.

PRODUCT FEATURES AND BENEFITS:

- Contains specialized ingredients to help protect seals and O-rings and provide smooth shifting at low and high temperatures
- Low oxidation rate helps to extend fluid change intervals
- Specially formulated for vehicles with Z1 transmissions with codes MJ7 and MJ8

Automatic Transmission Seal Conditioner



Container Size Unit Package ACDelco Part Number GM Part Number 12 oz. 12 10-3008 88861314

PRODUCT DESCRIPTION AND FUNCTION:

Automatic Transmission Seal Conditioner is designed to stop minor leaks or seepage of transmission fluid at the seals in automatic transmissions. This fluid contains seal swell, antioxidant, and dispersant additives often used in formulating automatic transmission fluids. This product is only for use in automatic transmissions using DEXRON-III or DEXRON-VI fluids.

PRODUCT FEATURES AND BENEFITS:

- Contains additives that soften then swell transmission seals to help fix and guard against minor fluid leaks and fluid seepage
- Designed to keep transmission shifting smoothly and help eliminate the need for major repairs
- Formulated specifically for use in automatic transmissions using DEXRON-III or –VI fluids

AW-1 Automatic Transmission Fluid



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 32 oz. | 1 | 10-4062 | 19256039 |

PRODUCT DESCRIPTION AND FUNCTION:

AW-1 Automatic Transmission Fluid is specially formulated for use in a relatively small set of GM vehicles. It is designed to meet the unique demands of a particular transmission type. AW-1 Automatic Transmission Fluid is a special application specific fluid for use in the 2010 and 2011 Cadillac SRX with LF1. It is designed for use in Aisin Warner transmissions. This fluid is not approved for use where DEXRON®-VI Automatic Transmission Fluid is recommended.

PRODUCT FEATURES AND BENEFITS:

- Excellent foaming and oxidation resistance provides protection against wear in the clutch and gears
- Specifically formulated for us in the 2010 and 2011 Cadillac SRX with LF1
- Designed to meet the unique demands of the Aisin Warner transmissions

BOT 303 Manual Transmission Fluid GL-4 (SAE 70W)



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 32 oz. | 6 | 10-4037 | 19259104 |

PRODUCT DESCRIPTION AND FUNCTION:

BOT 303 Manual Transmission Fluid, SAE 70W GL-4 is a high quality manual transmission fluid. It is specifically designed to provide good shifting movements and transmission efficiency in cold weather. WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

PRODUCT FEATURES AND BENEFITS:

- High-quality manual transmission fluid
- Specifically formulated to provide good shifting movements
- Manufactured for transmission efficiency in cold weather

CVT Fluid



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 32 oz. | 12 | 10-4092 | 19260800 |

PRODUCT DESCRIPTION AND FUNCTION:

CVT (Continuously Variable Transmission) Fluid is critical in ensuring the proper operation and maintenance of GM CVTs. CVTs are 'step-less', lacking the gears of a traditional automatic transmission, and the use of this fluid will assist in guaranteeing the CVT's advantages in efficiency. The continuously variable transmission fluid specifications are a function of the design parameters for the transmission. Each CVT has its own specific requirements. Not all CVT fluids are the same. Check owner manual for proper application.

- Specific coefficient of friction intended only for CVTs ensures smooth ratio changes without power interruption, enables engine to remain at its maximum power RPM, and provides for consistent, uninterrupted acceleration
- Fluid is colored green (as opposed to traditional red transmission fluids) to provide for simple visual identification of proper fluid for CVT-specific use
- Use of this product assists in guaranteeing the CVT's advantages in efficiency



CVT Fluid

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 1 gal. | 6 | 10-4097 | 19303860 |

PRODUCT DESCRIPTION AND FUNCTION:

CVT (Continuously Variable Transmission) Fluid is critical in ensuring the proper operation and maintenance of GM CVTs. CVTs are 'step-less', lacking the gears of a traditional automatic transmission, and the use of this fluid will assist in guaranteeing the CVT's advantages in efficiency. The continuously variable transmission fluid specifications are a function of the design parameters for the transmission. Each CVT has its own specific requirements. Not all CVT fluids are the same. Check owner manual for proper application.

PRODUCT FEATURES AND BENEFITS:

- Specific coefficient of friction intended only for CVTs ensures smooth ratio changes without power interruption, enables engine to remain at its maximum power RPM, and provides for consistent, uninterrupted acceleration
- Fluid is colored green (as opposed to traditional red transmission fluids) to provide for simple visual identification of proper fluid for CVT-specific use
- Use of this product assists in guaranteeing the CVT's advantages in efficiency

DEXRON® ULV Automatic Transmission Fluid



Container Size Unit Package ACDelco Part Number GM Part Number 32 fl. oz. 12 10-4107 19352619

PRODUCT DESCRIPTION AND FUNCTION:

DEXRON® ULV Automatic Transmission Fluid is an ultra-low viscosity automatic transmission fluid designed for use in modern passenger car and light truck transmissions. It is specially designed for use in 10 speed transmissions where a DEXRON® low viscosity automatic transmission fluid is specified. This product is formulated with unique high performance additives to provide excellent gear shifting and to guard against transmission shudder. It helps to increase fuel economy and provides long lasting transmission protection.

DEXRON® ULV Automatic Transmission Fluid is not a suitable

DEXRON®-VI Automatic Transmission Fluid



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 32 oz. | 12 | 10-9394 | 88865601 |

PRODUCT DESCRIPTION AND FUNCTION:

replacement for DEXRON® III or DEXRON®-VI.

DEXRON®-VI Automatic Transmission Fluid has a broad range of coverage in General Motors passenger car and light truck applications. However, it is recommended that the purchaser of this product verify in the vehicle Owner's Manual the manufacturer's specified transmission fluid and/or the use of this product in other than transmission related applications such as a power steering fluid. DEXRON®-VI replaces DEXRON®-III and DEXRON®-III-H. This fluid meets GMW16444 original equipment specification.

PRODUCT FEATURES AND BENEFITS:

- Backward compatible with previous DEXRON® automatic transmission fluids and can be used as a much-improved replacement for older vehicles/transmissions originally using previous DEXRON® fluids
- Improved performance over previous DEXRON® fluids in: friction durability, viscosity stability, aeration and foam control, and oxidation resistance
- Potential to enable improved fuel economy and longer transmission life

DEXRON®-VI Automatic Transmission Fluid



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 1 gal. | 3 | 10-9395 | 88865602 |

PRODUCT DESCRIPTION AND FUNCTION:

DEXRON®-VI Automatic Transmission Fluid has a broad range of coverage in General Motors passenger car and light truck applications. However, it is recommended that the purchaser of this product verify in the vehicle Owner's Manual the manufacturer's specified transmission fluid and/or the use of this product in other than transmission related applications such as a power steering fluid. DEXRON®-VI replaces DEXRON®-III and DEXRON®-III-H. This fluid meets GMW16444 original equipment specification.

PRODUCT FEATURES AND BENEFITS:

- Backward compatible with previous DEXRON® automatic transmission fluids and can be used as a much-improved replacement for older vehicles/transmissions originally using previous DEXRON® fluids
- Improved performance over previous DEXRON® fluids in: friction durability, viscosity stability, aeration and foam control, and oxidation resistance
- Potential to enable improved fuel economy and longer transmission life

DEXRON®-VI Automatic Transmission Fluid



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 55 gal. drum | 1 | 10-9396 | 88865603 |

PRODUCT DESCRIPTION AND FUNCTION:

DEXRON®-VI Automatic Transmission Fluid has a broad range of coverage in General Motors passenger car and light truck applications. However, it is recommended that the purchaser of this product verify in the vehicle Owner's Manual the manufacturer's specified transmission fluid and/or the use of this product in other than transmission related applications such as a power steering fluid. DEXRON®-VI replaces DEXRON®-III and DEXRON®-III-H. This fluid meets GMW16444 original equipment specification. For Professional Use Only. Not for Retail Sale.

- Backward compatible with previous DEXRON® automatic transmission fluids and can be used as a much-improved replacement for older vehicles/transmissions originally using previous DEXRON® fluids
- Improved performance over previous DEXRON® fluids in: friction durability, viscosity stability, aeration and foam control, and oxidation resistance
- Potential to enable improved fuel economy and longer transmission life



Manual Transmission and Transfer Case Fluid

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 32 oz. | 12 | 10-4033 | 88861800 |

PRODUCT DESCRIPTION AND FUNCTION:

Manual Transmission and Transfer Case Fluid is a conventional petroleum-based manual transmission fluid that provides effective protection for a wide range of vehicles. This fluid has significantly improved oxidation resistance when compared to previous fluids. WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

PRODUCT FEATURES AND BENEFITS:

- Conventional petroleum-based manual transmission fluid formulated to provide protection for a wide range of vehicles
- Significantly improved oxidation resistance when compared to previous fluids
- · High quality manual transmission fluid

Manual Transmission Fluid GL-3 (75W-90)



Container SizeUnit PackageACDelco Part NumberGM Part Number1.06 Quart1210-411319354435

PRODUCT DESCRIPTION AND FUNCTION:

Manual Transmission Fluid is engineered to meet the most demanding extended drain and warranty requirements. This product is designed for use in heavy-duty drivetrains that require gear lubricants with relatively high viscosity and excellent load carrying capability and where extreme pressures and shock loading is expected.

Manual Transmission Fluid GL-4 (75W-85)



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 32 fl. oz. | 1 | 10-4104 | 19351859 |

PRODUCT DESCRIPTION AND FUNCTION:

Manual Transmission Fluid GL-4 (75W-85) is a high-performance gear oil for manual transmissions. The carefully balanced additive system forms a long-life lubricant. Manual Transmission Fluid GL-4 (75W-85) has a balance of viscosity and frictional properties that ensure good shift feel and fast gear change in cold temperature.

Manual Transmission Fluid GL-4 (SAE 75W-85)



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|-----------------------|
| 32 oz. | 6 | 10-4055 | 88862472 |

PRODUCT DESCRIPTION AND FUNCTION:

Manual Transmission Fluid GL-4 (75W-85) is a high-performance gear oil for manual transmissions. The carefully balanced additive system forms a long-life lubricant. Manual Transmission Fluid GL-4 (75W-85) has a balance of viscosity and frictional properties that ensure good shift feel and fast gear change in cold temperature.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

PRODUCT FEATURES AND BENEFITS:

- High-quality manual transmission fluid
- Provides superior protection for transmission components in a variety of vehicle types
- Formulated to maintain high performance characteristics, even in cold weather

Synchromesh Transmission Fluid



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 32 oz. | 12 | 10-4006 | 88900333 |

PRODUCT DESCRIPTION AND FUNCTION:

Synchromesh Transmission Fluid is a synthetic blend manual transmission fluid designed specifically for use in GM New Venture NV3500 manual transmissions. This fluid has excellent lubrication properties that prevent breakdown over time.

- Formulated specifically for synchromesh transmissions, resulting in excellent synchronizer performance
- Minimizes sludge and varnish deposits to provide for a cleaner transmission
- Protects against surface distress, minimizing spalling, pitting, rust, corrosion, and overall wear



Synchromesh Transmission Fluid-Friction Modified

| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 32 oz. | 6 | 10-4014 | 88900399 |

PRODUCT DESCRIPTION AND FUNCTION:

Synchromesh Transmission Fluid-Friction Modified is a synthetic blend manual transmission fluid designed specifically for use in GM manual transmissions. This fluid has excellent lubrication properties that prevent breakdown over time and reduce friction to minimize transmission wear. This synchromesh transmission fluid is for use only in New Venture NV1500 manual transmissions. See service manual for GM vehicle application.

PRODUCT FEATURES AND BENEFITS:

- Formulated specifically for synchromesh transmissions, resulting in excellent synchronizer performance
- Minimizes sludge and varnish deposits to provide for a cleaner transmission
- Protects against surface distress, minimizing spalling, pitting, rust, corrosion, and overall wear

Synthetic Manual Transmission Fluid GL-4 (75W-85)



Container SizeUnit PackageACDelco Part NumberGM Part Number32 oz.610-411919369226

PRODUCT DESCRIPTION AND FUNCTION:

Synthetic Manual Transmission Fluid, 75W-85 GL-4 is a high quality, fully synthetic fluid. This fluid provides superior protection, enabling quicker shifting and prolonging the life of transmission components. WARNING: Cancer - www.P65Warnings.ca.gov.

PRODUCT FEATURES AND BENEFITS:

- Superior thermal and oxidation stability helps fluid withstand high temperatures and extreme pressure during constant use
- High-quality synthetic fluid provides superior protection
- Use of product enables quicker shifting and prolongs the life of transmission components

Synthetic Transmission Fluid



| Container Size | Unit Package | ACDelco Part Number | GM Part Number |
|----------------|--------------|---------------------|----------------|
| 32 oz. | 12 | 10-4029 | 12378515 |

PRODUCT DESCRIPTION AND FUNCTION:

Synthetic Manual Transmission Fluid is a high viscosity index synthetic base fluid that provides superior low to high temperature performance. This fluid can be used year-round in all climates. For GM vehicles, this product is specially formulated for the manual ZF 6-speed transmission in CK trucks with RPO ML6. WARNING: Cancer - www.P65Warnings.ca.gov.

PRODUCT FEATURES AND BENEFITS:

- Excellent thermal, oxidation, and shear stability and high resistance to foaming and corrosion: resists deposit formation and provides for extended drain intervals
- Specifically formulated for the manual ZF 6-speed transmission in CK trucks with RPO ML6
- All-climate fluid provide superior low to high temperature performance

WS-ATF Automatic Transmission Fluid



| 711 71410114110 114110111001011 11414 | | | | | | |
|---------------------------------------|--------------|---------------------|----------------|--|--|--|
| Container Size | Unit Package | ACDelco Part Number | GM Part Number | | | |
| 32 oz. | 12 | 10-4049 | 88863400 | | | |

PRODUCT DESCRIPTION AND FUNCTION:

WS-ATF (WS refers to World Standard) is a unique automatic transmission fluid that does not have compatibility with any other ATFs. With low viscosity at normal engine temperatures, this product has the potential to improve fuel economy.

- Uniquely formulated transmission fluid does not have compatibility with any other Automatic Transmission Fluids
- High quality, low viscosity at normal engine temperatures
- World Standard product has the potential to improve fuel economy

ACCIDENTAL EXPOSURE TO GM CHEMICAL CONTAINING PRODUCTS

General Motors Company distributes various chemical products that could potentially be harmful in the event of accident exposure.

Questions regarding exposure may be answered by calling the following number:

24/7/365 GM SECURITY GLOBAL CRISIS CENTER 1-800-814-3390

SAFETY DATA SHEET (SDS)

Safety Data Sheets (SDSs) are provided as a requirement by the Federal Agency, the Occupational Safety and Health Administration (OSHA). This standard is often referred to as the "Hazard Communication Law" (29. CFR. 1910.1200).

Dealers and wholesalers are advised to consult their legal counsel for assistance regarding the application of this standard, as well as relevant local and state requirements applicable to their particular operations.

Under the existing rule, Parts Department personnel may be required to provide SDSs to their customers who purchase hazardous chemicals per the requirements of Federal, State or Local Regulations.

When a retail customer purchases a chemical product from you and requests an SDS, it is your responsibility to supply a copy.

When a customer is a body shop, service station, garage, or other business concern that uses chemical products purchased from you in repair of a car, truck, bus, SUV, etc., a copy of the appropriate SDS(s) should be supplied automatically as part of the sale. SDSs should, therefore, be kept in an area accessible to your employees.

To locate a Safety Data Sheet:

- 1. Access Global Connect
- 2. Choose the Department tab
- Select 'Parts'
- 4. Under Applications choose Filter
- 5. Choose 'Reports'
- 6. Click on the EPIC Application
- 7. Under Periodical Reference, click Inquiry
- 8. In the keyword box, enter the GM part number and in the "publication type" drop-down, select SDS
- 9. Click search and the sheet you need will appear

BLANK

BLANK

| Hala wasa asata | omers get the mos | st from their invest | ment with genuine A | CDelco |
|------------------|-------------------|----------------------|---------------------|-----------|
| automotive fluid | ds and chemicals | . Specially formulc | ated to keep Americ | a moving. |
| automotive fluid | ds and chemicals | . Specially formula | ated to keep Americ | a moving. |
| automotive fluid | ds and chemicals | . Specially formula | ated to keep Americ | a moving. |

